

# INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

## CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

## GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

## ASSEMBLY AND INSTALLATION

1. Thread the 3" Rod onto the Coupling at the top center of the fixture body, connect 1\*3" Rod, 1\*6" Rod, 3\*12" Rod together with Couplings. Then use quick link to connect Canopy to Loop and the top 12" Rod.
2. Thread the Support screws to the cross bar and secure with the Hex nut.
3. Secure the Cross bar to the outlet box with the Mounting screws.
4. Pull out the outlet wire and ground wire from the Outlet Box.
5. Make wire connections:
  - The ridged wire (unmarked) from the fixture to white wire from power source.
  - The smooth wire (marked) from the fixture to black wire from power source.
  - Attach the ground wire to cross bar with a green screw.
6. Place the canopy over the outlet box and secure the canopy with Ball nut.
7. Install bulbs: (Bulbs not included). (Don't exceed the maximum capacity that recommended on the sockets).

INSTALLATION IS NOW COMPLETED.

