

# ASSEMBLY INSTRUCTIONS



## CAUTION

◆ Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

◆ Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

## TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape




Phillips screwdriver



Flat blade screwdriver



Pliers




Wire strippers


## HARDWARE INCLUDED



Fixture



Cage



Mounting Unit



Ball Nuts




Mounting Screws



Wire Nuts

**\*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**


## EXPLODED PARTS



## INSTALLATION



### STEP 1

Unscrew the **ball nuts** from the **mounting unit**. Use the **mounting screws** to attach the **mounting unit** to the junction box (not included).



### STEP 2

Make the electrical connection from the junction box (not included) to the **fixture**. Connect the ground wire to the **mounting unit** using the preinstalled green ground screw. Next, connect the live wire, neutral wire and ground wires with the supplied **wire nuts**. Secure with electrical tape.




# ASSEMBLY INSTRUCTIONS (INSTALLATION)

## STEP 3


Attach the **fixture** to the **mounting unit** through screws holes as shown, and secure it with **ball nuts**.

\*Junction Box  
(not included)




## STEP 4

Remove the **socket ring** from the socket.  
Use the **socket ring** to attach the **cage** to the **fixture**.



## STEP 5

Install bulb (not included)



BULB BASE TYPE  
Medium (E26)