



2*E26 Max 40W Not included



Howard Double Wall Sconce Instruction

Safety Warning

Turn OFF power at the breaker panel and verify the wires are not live before beginning.

Installation Steps

- **Step 1: Attach the Mounting Plate**

Attach the round mounting plate to the wall junction box with the two #8-32 screws supplied. The two threaded posts must face outward and sit level.

- **Step 2: Wire the Fixture**

Wire the fixture body:

1. Connect black (hot) to black, white (neutral) to white, and green/bare (ground) to green/bare or the ground screw on the plate.
2. Twist connectors clockwise and tuck all splices neatly inside the box.

- **Step 3: Mount the Fixture Body**

Place the fixture body onto the mounting plate, aligning it with the threaded posts, and press firmly against the wall.

- **Step 4: Tighten the Locking Screw**

Secure the fixture by tightening the vertical screw until the fixture body is firmly attached to the mounting plate.

- **Step 5: Install the E26 Bulbs**

Install two E26 bulbs (max 40W each, not included) by screwing them clockwise into the sockets until secure.

- **Step 6: Position the Glass Shades**

Carefully slide the cylindrical glass shades over both sockets, ensuring they are properly aligned with the fixture housings.

- **Step 7: Secure the Shades with Retaining Rings**

Secure the glass shades by tightening the retaining rings onto each socket. Hand-tighten only to avoid cracking the glass.

Final Check

Restore power at the breaker panel and test the sconce. Both bulbs should illuminate evenly and the glass shades should be secure with no wobble.

Please contact us if you have any problems installing the lampshade. We will work you through the process.