



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1520 - 120/100/80 Wattage Selectable LED UFO High Bay; 3K/4K/5K CCT Selectable; 60/80/100 Beam Angle Selectable; Black Finish; 120-347 Volt

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	120W/100W/80W
Volts:	120V-347V
Lumens:	12501L-19837L
Lamp Base :	Integrated - Integrated
CRI:	80
Rg Value :	9
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	60/80/100
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Incandescent Equivalent :	500W-800W
HID Equivalent :	150W-250W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 6KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PHYSICAL

Finish:	Black
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Dimensions:	H:7.84" DIA:11.81"
Weight (Lbs.):	5.07
Material:	Die-Cast Aluminum

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-QBQLLW
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923412509
Each Quantity:	1
Each Dimensions:	14.17 x 14.17 x 6.50

INFO

Specification Note:	Default Wattage: 120W
---------------------	-----------------------

ACCESSORIES

	65-169	Whip Connector; 5,5 Foot; IP68 Rated; Black; 0-10V Dimming
	65-199	Whip Connector; 5,5 ft.; IP68 Rated; Supply Line Voltage; Black
	65-765	Yoke Mount Bracket; Black Finish; For Use With Gen 2 100W/150W & CCT & Wattage Selectable UFO High Bay Fixtures
	65-769	3/8" to 3/4" Pendant Adapter; Black Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures
	65-778	Add-On Aluminum Reflector; Use with 100W & 150W Gen 2 UFO LED High Bay Fixtures
	65-780	Add-On EM Battery Backup; For use with Gen 2 100W/150W and 65/770R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 30 Watt /90 Min Run Time
	65-790	Add-On Bottom Diffuser for 100W & 150W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-789 (PC Shade) and 65-811
	65-811	Add-On PC Shade; Use with 100W & 150W UFO LED High Bay Fixtures
	65-834	DOMINO; Protective Wire Guard; 120W UFO High Bay
	86-237	Programming Remote for PIR Sensors; 86-238 and 86-239
	86-238	Add On PIR Sensor; 12 Meter; Must Use Remote 86-237
	86-239	Add on Microwave Sensor; 15 Meter; Must Use Remote 86-237