

Cat Cage Quality Inspection Standards

Product Name	Pink Cat Cage	
Factory Name	Tangshan Jichangbao Pet Products Co., Ltd	
SKU	GC-FBA-323L	
Sampling standard	GB2828.1/S-3/AQL4.0	

Size and weight 87*63*18CM 19.552KG

Quality inspection type	Number	Quality inspection standard	Sampling number	Result
Finished product stacking and placement	1	Confirm the placement of finished products in the warehouse and check if the goods pile is in good condition; Is there any deformation caused by cardboard box compression	Order quantity	Qualified
	2	The product should not be placed directly on the ground to prevent moisture and mold	Order quantity	Qualified
	3	Do not let the cardboard box exceed the edge of the pallet. In special circumstances, it can exceed the two sides of the pallet facing each other, with a	Order quantity	Qualified

		maximum of 2.5cm on each side (try to avoid it).		
	4	Count the quantity and require packaging to complete more than 80% of the quantity reported on the inspection report	Order quantity	Qualified
packaging inspection	5	The outer packaging box is free from damage, moisture, mold, deformation, dirt, etc	AQL 4.0	Qualified
	6	The outer box needs to be sealed with tape, pasted flat, and cannot cover barcode and other information	AQL 4.0	Qualified
	7	Do not use strapping	AQL 4.0	Qualified
	8	According to the developer's requirements, check whether the packaging printing content is correct or not	AQL 4.0	Qualified
	9	There should be no obvious exposed Chinese markings	AQL 4.0	Qualified
Product weight and packaging dimensions	10	Packaging size: The system indicates a length, width, and height within ± 1 cm (including 1cm), such as 10 ± 1 cm, with a range of 9-11cm- Measure 3 pieces and take the average value (finished product inspection)	5PCS	Qualified

	11	Gross weight/net weight: System standard weight $\pm$ 5% deviation (including 5%), and absolute weight $\pm$ 2kg deviation (including 2kg)- Measure 3 pieces and take the average value (finished product inspection)		Qualified
label	12	The label font is clear, the label content, format, and numbers are error free, and the barcode can be scanned normally	Sampling quantity	Qualified
	13	The label should be pasted neatly and uniformly, with clear and visible barcodes and no wavy stripes. Do not stick the label on the curved parts or corners of the package, leaving at least 0.25 inches (0.64cm) of clearance between the label edge and the packaging edge		Qualified
	14	Do not repeat labeling; Don't label less		Qualified
	15	The label cannot be covered by tape		Qualified
	16	Require the use of a carbon ribbon printer or copperplate paper label printing --All barcode labels must be able to be scanned and remain scannable for 24 months. Factories can use printing equipment that meets this requirement based on their own conditions		Qualified

Packaging drop box	17	According to the requirements of the procurement agreement, drop the box according to the standard <table border="1"> <caption>重量<60kg (150Lb) 跌落标准 (适用包装类型: 箱型, 扁平型, 长条型) 测试方式详见下表</caption> <thead> <tr> <th>跌落</th><th>跌落高度</th><th>跌落面</th><th>测试部位</th><th>测试形式</th></tr> </thead> <tbody> <tr> <td>1</td><td>100mm (24inch)</td><td>400mm (16inch)</td><td>3-4 角</td><td>自由跌落</td></tr> <tr> <td>2</td><td>400mm (24inch)</td><td>400mm (16inch)</td><td>3-4 角</td><td>自由跌落</td></tr> <tr> <td>3</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>4-5 角</td><td>自由跌落</td></tr> <tr> <td>4</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>2-4-5 角</td><td>自由跌落</td></tr> <tr> <td>5</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>2-3-5 角</td><td>自由跌落</td></tr> <tr> <td>6</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>2-3 角</td><td>自由跌落</td></tr> <tr> <td>7</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>1-2 角</td><td>自由跌落</td></tr> <tr> <td>8</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>2 面</td><td>自由跌落</td></tr> <tr> <td>9</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>1 面</td><td>自由跌落</td></tr> <tr> <td>10</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>1-3 角</td><td>自由跌落</td></tr> <tr> <td>11</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>2 面</td><td>自由跌落</td></tr> <tr> <td>12</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>4 面</td><td>自由跌落</td></tr> <tr> <td>13</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>5 面</td><td>自由跌落</td></tr> <tr> <td>14</td><td>800mm (24inch)</td><td>400mm (16inch)</td><td>6 面</td><td>自由跌落</td></tr> </tbody> </table>	跌落	跌落高度	跌落面	测试部位	测试形式	1	100mm (24inch)	400mm (16inch)	3-4 角	自由跌落	2	400mm (24inch)	400mm (16inch)	3-4 角	自由跌落	3	800mm (24inch)	400mm (16inch)	4-5 角	自由跌落	4	800mm (24inch)	400mm (16inch)	2-4-5 角	自由跌落	5	800mm (24inch)	400mm (16inch)	2-3-5 角	自由跌落	6	800mm (24inch)	400mm (16inch)	2-3 角	自由跌落	7	800mm (24inch)	400mm (16inch)	1-2 角	自由跌落	8	800mm (24inch)	400mm (16inch)	2 面	自由跌落	9	800mm (24inch)	400mm (16inch)	1 面	自由跌落	10	800mm (24inch)	400mm (16inch)	1-3 角	自由跌落	11	800mm (24inch)	400mm (16inch)	2 面	自由跌落	12	800mm (24inch)	400mm (16inch)	4 面	自由跌落	13	800mm (24inch)	400mm (16inch)	5 面	自由跌落	14	800mm (24inch)	400mm (16inch)	6 面	自由跌落	1PC	Qualified
跌落	跌落高度	跌落面	测试部位	测试形式																																																																											
1	100mm (24inch)	400mm (16inch)	3-4 角	自由跌落																																																																											
2	400mm (24inch)	400mm (16inch)	3-4 角	自由跌落																																																																											
3	800mm (24inch)	400mm (16inch)	4-5 角	自由跌落																																																																											
4	800mm (24inch)	400mm (16inch)	2-4-5 角	自由跌落																																																																											
5	800mm (24inch)	400mm (16inch)	2-3-5 角	自由跌落																																																																											
6	800mm (24inch)	400mm (16inch)	2-3 角	自由跌落																																																																											
7	800mm (24inch)	400mm (16inch)	1-2 角	自由跌落																																																																											
8	800mm (24inch)	400mm (16inch)	2 面	自由跌落																																																																											
9	800mm (24inch)	400mm (16inch)	1 面	自由跌落																																																																											
10	800mm (24inch)	400mm (16inch)	1-3 角	自由跌落																																																																											
11	800mm (24inch)	400mm (16inch)	2 面	自由跌落																																																																											
12	800mm (24inch)	400mm (16inch)	4 面	自由跌落																																																																											
13	800mm (24inch)	400mm (16inch)	5 面	自由跌落																																																																											
14	800mm (24inch)	400mm (16inch)	6 面	自由跌落																																																																											
Unboxing inspection	18	The internal packaging filling of the product meets the requirements	1PC	Qualified																																																																											
	19	PE plastic bag anti suffocation requirements: When the opening size of the plastic bag used for product packaging is $\geq 12.5\text{CM}$, this anti suffocation warning label must be printed or posted on the plastic bag. At the same time, the plastic bag must have at least 2 through holes with a diameter of not less than 1CM and a maximum diameter of not more than 1.5CM	Sampling quantity	Qualified																																																																											
Manual	20	Does the product manual match the product		Qualified																																																																											

	21	Check if the accessories are consistent with the manual		Qualified
Appearance	22	The surface is free of scratches, dirt, pitting, discoloration, oxidation, flash, cracking, roughness and other adverse phenomena;	1PC	Qualified
Assembly testing	24	All components can be assembled smoothly without any poor fit	5PCS	Qualified
	25	Door opening and closing test	5PCS	Qualified
Product dimensions	26	Product size inspection: 32.2*23.2*64.6in (82*59*163cm)	5PCS	Qualified
Historical customer complaints	27		5PCS	Qualified













