## ADJUSTABLE STEEL GANTRY CRANE - KNOCKDOWN - AHSN-6-20-14 APPROX WEIGHT: 1434,20 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!! \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 6 1/2"-- 239 3/4" -12 5/16" 229 1/4" 181 1/4" 169" MAX 3D VIEW FOR 103" MIN REFERENCE ONLY DIMENSION TOLERANCE ± 1/4" I. THE UNDERSIGNED. AGREE THAT THE PRODUCT AS STANDARD FEATURES SPECIAL FEATURES REPRESENTED SATISFIES DESIGN AND DIMENSION MODEL NUMBER IS AHSN-6-20-14 REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO NONE Α CONFIRM PRODUCT AND INSTALLATION CAPACITY IS 6,000 LBS. P COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE P BASE WIDTH IS 88" AND LOCAL REGULATIONS AND STANDARDS. R MAX OVERALL HEIGHT IS 181 1/4" ANY MODIFIED UNITS ARE NON-RETURNABLE 0 I-BEAM HEIGHT IS 12 5/16" [ ] As drawn [ ] As marked I-BEAM FLANGE WIDTH IS 6 1/2" Signed: Date: OVERALL I-BEAM LENGTH IS 239 3/4" Printed Name: USABLE I-BEAM LENGTH IS 209 3/4" LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING ADJUSTABLE UNDER I-BEAM HEIGHT DISTRIBUTOR'S NAME: FOR INTERNAL USE ONLY 169" MAX W.O.# X PROJECT SIGN OFF VESTIL MANUFACTURING 103" MIN **SALES** DRAWN BY: DLS HEIGHT IS ADJUSTABLE IN 6" INCREMENTS DATE: 07/22/2014 SALES: X CASTERS: (4) Ø8" X 3" WIDE PHENOLIC ENG. reference: X SCALE: 1:50 FILE NAME: SWIVEL CASTERS WITH FOUR FAB. LOCKING POSITIONS QUOTED LEAD TIME: $_{ m Y}$ QUOTE # 28-007-332 POWER Χ