



PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

IMPORTANT:

1. **WARNING** - Disconnect power before relamping or wiring the fixture. Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

INSTALLATION STEPS:

- 1-3. Screw the straight rod tightly onto the threaded nipple on top of the lamp body, then securely attach the hanging ring to the straight rod.
- 4-7. Adjust the length of the hanging chains according to the desired height of the fixture. Ensure that both chains are of equal length, then use swivel snaps to connect the lamp body, chains, and ceiling plate together.
- 8-9. Secure the mounting bracket to the junction box with mounting screws.
10. Inside the junction box, connect the wires using wire connectors as follows:
 Fixture BLACK wire to home LIVE wire.
 Fixture WHITE wire to home NEUTRAL wire.
11. Fix the fixture ground wire and home ground wire to the mounting bracket using green screws. Carefully tuck wires back into the junction box.
12. Cover the ceiling plate(7) on the mounting bracket, and then tighten the nut(12) to fix the ceiling plate.
- 13 Install the bulbs (not included).