

PRODUCT FEATURES

- Modern Style
- Lighting designed to project modern simplicity
- Illuminates a smooth wash of light through an LED diffuser
- Protected by a 5-year warranty. Please visit the "About Us" Page on techlighting.com for more for warranty details
- Available in modern finishes



LAMPING

Includes 120-277 volt 21.1 watts, 899 total delivered lumens, 3000K LED module. Dimmable with most LED compatible ELV and TRIAC dimmers. Ceiling mount only.

Nightshade Black Alt View



Nightshade Black

Nightshade Black
Alt View

Matte White

Matte White
Alt View

ORDERING INFORMATION

700FMKOSA LENGTH (A)	FINISH	LAMP
18 18"	W MATTE WHITE B NIGHTSHADE BLACK	-LED930 INTEGRATED LED 90 CRI 3000K 120V-277V UNV

700FMKOSA _____

JOB NAME _____


NOTES _____



KOSA 18 CEILING

SPECIFICATIONS

HARDWARE MATERIAL	Metal
SHADE MATERIAL	Acrylic
NET WEIGHT	5 lbs
HEIGHT	4.6in
WIDTH	18in
LENGTH	18in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	Yes
DRY LISTED	
WALL / CEILING MOUNT	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		899		
WATTS		21.1		
MAX WATTAGE PER BULB		21.1W		
INPUT VOLTAGE		Universal 120V-277V		
DIMMING TYPE*		ELV, TRIAC		
CCT		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

*Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8 .	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

