

BACKSPLASH TILES 12"x 3"

GFRC TILE USE & CARE GUIDE

USE

To determine appropriate uses of the product, carefully inspect the specifications section of the product page. Pay extra attention to the following factors:

Every tile has a P.E.I. rating that indicates how wear-resistant a tile is on a scale of 0 to 5. The higher the rating, the more durable the tile is. For example, a PEI rating of class 0 should not have any foot traffic at all; it's strictly for wall installations.

Our concrete tiles are cast using a Glass Fiber Reinforced Concrete (GFRC) matrix, a high performance concrete that allows the panels to be made lighter, stronger and thinner. Our GFRC wall tiles are typically made at 5/8" - 1" thick. Since there are no stone aggregates or metal reinforcing within a standard wall panel, GFRC can be cut as easily as natural stone tile allowing you to order one generic size for efficiency.

Durability – GFRC combines cement, Alkali resistant fiberglass, and other aggregate minerals to strengthen the material. That strength and durability makes it ideal for both, exterior and interior use. GFRC is waterproof and fireproof. It makes it ideal for harsher climates that see a lot of frost and colder weather. In milder climates, either material is suitable.

CARE

Tile is low-maintenance surface choice for your home. Its care is simple and cost-effective and will keep tile looking brand new, lustrous and scratch-free. Here are some tips on how to maintain a tile care:

Regular Clening:

Sweep the tile free of dirt and dust (or in the case of backsplashes/wall installations, wiping with dry cloth) at least twice a week.

Deeper cleaning:

Use soap and warm water-other products can dull the glaze! Make sure to use non abrasive materials, like cloth rather than the rough side of a sponge.

For grout lines:

Use warm soap and water with a stiff-bristled toothbrush. For particularly stubborn mold, mildew, or soap scum, use watered-down distilled white vinegar. We recommend one part vinegar and one part water, contained in a spray bottle. If needed, briefly leave the mixture on the grout line before cleaning.