
## **ENTRYWAY STORAGE BENCH**





# FOR REPLACEMENT PARTS OR HELP WITH ASSEMBLY PLEASE CONTACT US

PLEASE ENSURE TO HAVE THE MODEL #
FROM THE PACKAGING OR INSTRUCTION BOOKLET

TO RETURN THE PRODUCT:

PLEASE CONTACT THE RETAILER

WHERE THE ITEM WAS PURCHASED FROM

**IMPORTANT**: Please read this manual carefully before beginning assembly of this product. Keep this manual for future reference.

## **SAFETY INFORMATION**

Identify all the parts and hardware. Do not discard of the packaging until you have checked that you have all of the parts and hardware required. Hardware package may have spare parts.

**WARNING:** This item contains small parts which can be swallowed by children and pets. Keep children and pets away during assembly. To avoid danger of suffocation, always keep plastic bags away from children and pets. We recommend that you assemble this unit on a carpeted floor to avoid scratches. If using power tools, set the tool to low torque to avoid damage.

May require 2 people for ease of assembly.

## **CARE and MAINTENANCE**


To clean, use a soft or slightly damp cloth, then wipe with a clean, dry cloth. Dust with soft dry cloth.


Do not use ammonia-based cleaning products, as they will damage the finish.


Do not leave liquids or damp cloths on this furniture.

To avoid dulling of the finish, do not place furniture in direct sunlight.


Please inspect and tighten all screws or bolts on a regular basis to ensure proper performance and safety of your item.








#### STEP 1



- 1. Insert Dowel (6) into Divider (C).
- 2. Use rubber mallet to tap Dowels 6 into bottom of holes securely. 1/2 length of Dowels should be exposed.
- 3. Align pre-drilled holes on bottom of Back F with Dowel 6 on Divider C. (Note: please pay close attention to the location of the 2 small guide holes which accommodate the lid support. They need to be on the same side as the hinges).
- 4. Using 2 Allen Key Screws 3 to attach Back F to Divider C.

## STEP 2




1. Attach Bottom Panel G to Divider C & Back F by sliding on the gap between Divider C & the long rail on Back F.

#### STEP 3




**NOTE**: The screwdriver is not included in the hardware pack.




- 1. Insert Dowel 6 into Divider C.
- 2. Use rubber mallet to tap Dowels 6 into bottom of holes securely. 1/2 length of Dowels should be exposed.
- 3. Align pre-drilled holes on bottom of Front Dwith Dowel 6 on Divider C.
- 4. Using 2 Phillips Screws 8 to attach Divider C to the middle bar on Front D.

#### STEP 4




- 1. Insert 4 Dowels 6 into each Side A at specified location.
- 2. Use rubber mallet to tap Dowels (6) into bottom of holes securely. 1/2 length of Dowels should be exposed.
- 3. Align pre-drilled holes on side bars of Front D & Back F with Dowel 6 on each Side A.
- 4. Using 4 Allen Key Bolts 1 (40mm length ) to attach Front D & Back F to each Side A.


#### STEP 5




**NOTE**: The screwdriver is not included in the hardware pack.



- 1. Attach Bottom Support Leg  $\widehat{H}$  into pre-drilled holes of Bottom Panel  $\widehat{G}$  using 4 Phillips Screws  $\widehat{8}$  .
- 2. Use Phillips screwdriver to tighten Screws. Do not over-tighten.




- 1. Attach Seat B to 3 Hinges on Back F using Phillips Screws 7 ( using guide holes underneath of Seat ).
- 2. Use phillips screwdriver to tighten Screws. Do not over-tighten.



- 1. Attach Lid Support 4 into pre-drilled holes of Seat B and Divider C using Phillips Screws Round Head 9.
- 2. Use phillips screwdriver to tighten Screws. Do not over-tighten.

## STEP 8



- 1. Attach Backrest (E) to back of Sides (A) using Allen Key Bolt (2) into pre-drilled holes.
- 2. Use Allen Key 5 to tighten Bolts. Do not over-tighten.

#### **WARRANTY**

Thank you for purchasing a product. These products have been made to demanding, high-quality standards and are guaranteed for domestic use against manufacturing faults for a period of 12 months from the date of purchase. This warranty does not affect your statutory rights.

In case of any malfunction of your product (failure, missing parts, etc.) please contact us at our toll free service line or email.

We reserve the right to repair or replace the defective product, at its discretion.

This product is guaranteed for 12 months if used for normal purposes. Any warranty is invalid if the product has been overloaded or subject to neglect, improper use or an attempted repair by other than an authorized agent. Heavy-duty or daily professional/commercial usage are not guaranteed.

Due to continuous product improvement, we reserve the right to change the product specifications without prior notice.