

# CHAIR


## ASSEMBLY INSTRUCTIONS

### PARTS AND PACKING CONFIGURATIONS


A. CHAIR BACK: 1 PC





B. FRONT LEG: 2 PCS



C. BACK LEFT LEG: 1 PC




D. BACK RIGHT LEG: 1 PC




### HARDWARE PACKED IN CARTON

No.	DESCRIPTION	PHOTO	QUANTITY
1	ALLEN BOLT ( $\frac{3}{8}$ " X 2")		4 PCS
2	ALLEN BOLT ( $\frac{3}{8}$ " X 1 $\frac{1}{2}$ ")		4 PCS
3	LOCK WASHER ( $\frac{3}{8}$ " )		8 PCS
4	FLAT WASHER ( $\frac{3}{8}$ " )		8 PCS
5	ALLEN KEY		1 PC

STEP 1:




STEP 2:




DO NOT TIGHTEN BOLTS COMPLETELY

STEP 3:



DO NOT TIGHTEN BOLTS COMPLETELY

STEP 4:



ON A FLAT, LEVEL SURFACE, PLACE THE CHAIR UPRIGHT AND LEVEL. WHEN LEVEL, PLEASE TIGHTEN ALL BOLTS FROM PREVIOUS STEPS WITH ALLEN KEY