



## Carpets for Kids® Mt. Shasta Solids Collection

YARN SPECIFICATIONS	
Description	Cut pile carpet
Traffic	Commercial
Warranty	Limited Lifetime Abrasive Wear
Fiber Type	100% BCF Nylon, Type N6

FABRIC FINISHING	
Dye Method	Piece Dyed
Soil Release	Carpet Guard

FABRIC CONSTRUCTION	
Finished Face Weight	30 oz. / sq. yd.
Yarn Ply	2-ply heat set
Stitches/Rows	9.0/inch
Gauge	1/10 ga.
Finished Pile Height	0.201 inches
Tufting Density	90.0/tufts/sq. inch
Primary Backing	Synthetic
Secondary Backing	Synthetic ActionBac

PERFORMANCE SPECIFICATIONS	
Density	5,373
<u>Traffic Performance</u>	
Static Electricity	<3.5 KV (AATCC-134)
Traffic	Recommended for commercial
<u>Flammability</u>	
Radiant Panel	>.45 watts/cm. sq. (ASTM-E648 <u>Class 1</u> )
NBS Smoke Chamber	<450 flaming & nonflaming (ASTM-E662 NFPA-253)
Methanimine Tablet	Self-extinguishing (DOC-FF-1)

ADDITIONAL SPECIFICATIONS	
Recycling	Carpet Fiber is recyclable



1. Specifications subject to normal manufacturing tolerances and may be changed without prior notice.
2. Serging is excluded from lifetime wear warranty.
3. Recycling includes all scraps, returned, and finished goods as necessary. Recycled back to carpet fiber or used in making other plastic materials like car parts.
4. Acceptance of orders subject to Carpets for Kids conditions of sale.