

Mats Inc. Technical Data for Berber Tile

Product Description

Material	100% solution-dyed UV stabilized polypropylene fibers
Backing	Bitumen
Tile Size	19-11/16" x 19-11/16" (50 cm x 50 cm) - approximately 2.7 sq ft per tile
Case Pack	20 tiles per case - 54 sq ft per case

Technical Specifications

	Test	Requirement	Berber Tile
Product Dimensions			
Pile height	ISO 1776	In inches	5/32"
Total height	ISO 1776	In inches	3/8"
Pile weight	ISO 8543	In ounces per square yard	33.9 oz/sq yd
Total weight	ISO 8543	In ounces per square yard	129.8 oz/sq yd
Safety			
Surface flammability	ASTM D2859 CPSC FF 1-70	Test specimen must be greater than 1" in at least 7 of 8 specimens tested	Passes
LEED			
MR Credit 4	LEED-NC v. 3	For 1 - 2 points: \$ value of <u>all</u> materials = min. average 10% recycled content	56.93% recycled (post-consumer)
IEQ Credit 4.1	LEED-NC v. 3	For 1 point: low-emitting adhesive with a VOC of 50 g/L or less for indoor carpet adhesive	Release-Bond VOC: 0 g/L
IEQ Credit 4.3	LEED-NC v. 3	For 1 point: low-emitting flooring per GreenLabelPlus or FloorScore™	GreenLabelPlus certified
IEQ Credit 5	LEED-NC v. 3	For 1 point: semi-permanently installed entrance system at least ten feet in length and maintained on a weekly basis by a contracted service organization	Berber Tile is designed for semi-permanent installation.