



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13510 - 12 Watt Commercial LED Downlight; 4 in.; Remote Driver; Watt and Color Selectable; 120-347 Volt

- Wattage Selectable
- CCT Selectable
- IC Rated
- Air Tight
- Flicker Free



ELECTRICAL

Technology:	LED
Watts:	12W/9W/6W
Volts:	120V-347V
Lumens:	1100L/900L/650L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	75W
Operating Temperature :	-25C (-13F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<30%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923135101
Each Quantity:	1
Each Dimensions:	7.68 x 4.13 x 7.01

INFO

Specification Note:	Default Wattage: 12W; FT6 cable between driver and lighting head; Default CCT: 3000K
---------------------	--

PHYSICAL

Finish:	Matte White
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:2.35" DIA:5.04"
Weight (Lbs.):	0.79
Material:	Aluminum












INSTALLATION

Sloped Ceiling Compatible:	No
----------------------------	----

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4515179
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
Vapor Tight Fixture Rated:	No
ADA Compliant:	No
Closet Rated:	No
FCC Compliant:	Yes
IP Rating:	IP54
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-865	4-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3.5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-943	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter
	80-950	New Construction Mounting Plate for Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter
	80-959	Rough-In Mounting Plate for 4/6/8 or 10 in. Commercial Downlight Fixtures
	80-985	6 FOOT REMOTE DRIVER 3-PIN EXT
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	S13520	Accessory for CDL Remote Driver - 4in rd matte clear/white trim
	S13521	Accessory for CDL Remote Driver - 4in rd matte clear trim
	S13522	Accessory for CDL Remote Driver - 4in rd matte black trim
	S13540	4" Flat Goof Ring for Commercial Downlights, Round, White Finish, 8.00 OD, 4.13 ID, 0.032 Thick.
