

Test Report

NUMBER : TSNH00565155

Applicant : Shenzhen Yuefeng Zhiqi Technology Co., Ltd.
A708-E1, 7th Floor, Block A, Building A, Jiangsu Building, No.
6013 Yitian Road, Fuxin Community, Lianhua Street, Futian
District, Shenzhen
Attn : TAN WEI HAO

Date : Oct 21, 2025

Photo:



To be continued

Authorized By :
For Intertek Testing Services
(Tianjin) Ltd.



David Zhang
Asst.General Manager



Test Report

NUMBER : TSNH00565155

Sample Description:

One (1) submitted sample said to be
 Item Name : Metal Loft Bed
 Item No. : BW00327
 Material : Metal
 Manufacturer : Shenzhen Yuefeng Zhiqi Technology Co., Ltd.
 Country of Origin : China

Tests Conducted:

As requested by the applicant, for details refer to attached page(s).

Conclusion:

<u>Tested Sample/Components</u>	<u>Standard</u>	<u>Result</u>
Submitted Sample	ASTM F1427-21 ^{e1} - Standard Consumer Safety Specification for Bunk Beds	Pass
Submitted Sample	16 CFR Part 1513 - Requirements for Bunk Beds Intended for Use by Children / 16 CFR Part 1213 -Requirements for Bunk Beds not Intended for Use by Children	Pass
Submitted Sample	Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels for Children Products	Pass
Submitted Sample	15 U.S.C. §2063(a)(5) (CPSA)	Pass
Submitted Sample	Consumer Product Safety Act Section 14(a) (5)	Pass
Submitted Sample	U.S. CFR Title 16 (CPSC Regulations) Mechanical and physical test	Pass
Submitted Sample	U.S. CFR Title 16 (CPSC Regulations) Part 1500.3(c)(6)(vi) flammability test on rigid and pliable solids	Pass
(1&6)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in surface coating	Pass

To be continued

Authorized By :
 For Intertek Testing Services
 (Tianjin) Ltd.



David Zhang
 Asst.General Manager



Test Report

NUMBER : TSNH00565155

(2&3),(4&5)&(7&8)	U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in non-surface coating materials (substrate)	Pass
(2&3),(4&5)&(7&8)	15 U.S.C. Sec. 1278a - Total Lead Content	Pass
(1&6)&(7&8)	US Consumer Product Safety Improvement Act 2008 Title I, Sec 108(a) & (b)(3) and US 16 CFR Part 1307 for Prohibition of Children's Toys and Child Care Articles Containing Specified Phthalates	See Comment

Comment: The testing scope of the standard was not applicable to the submitted samples. However, the test results of tested component(s) (1&6)&(7&8) did not exceed the limits of the standard.

To be continued

Authorized By :
For Intertek Testing Services
(Tianjin) Ltd.



David Zhang
Asst.General Manager



Test Report

NUMBER : TSNH00565155

1. Safety Specification for Bunk Beds

Reference standard: ASTM F1427-21^{e1} - Standard Consumer Safety Specification for Bunk Beds.

Number of sample tested: One (1) piece.


Executive summary:

Clause	Testing Items / Requirements	Assessment
1	Scope	--
2	Referenced Documents	--
3	Terminology	--
4	Performance Requirements	--
4.1	Vertical Protrusions	--
4.1.1	All vertical protrusions along the top inside surfaces of any individual component (including but not limited to bed end structures and guard rails) of the upper bunk shall not extend more than 3/16 in. (4.8 mm) above the upper edge of the adjacent surface. Ladder stiles (uprights) shall not extend more than 3/16 in. (4.8 mm) above the upper edge of the adjacent surface.	P
4.1.2	Any cap used along the top surface of the upper bunk shall not have a vertical protrusion greater than 3/16 in. (4.8 mm) at the edge of the protrusion above the upper edge of the adjacent surface. If the cap is flush with or overhangs the edge of the corner post or other vertical protrusion, the maximum vertical protrusion shall not exceed 3/16 in. (4.8 mm). The cap shall have a maximum height of no more than 20 % of the width or diameter of the cap. At no point shall the cap overhang the post more than 1/16 in. (2 mm). The cap shall fit flush with the top of the corner post.	P
4.2	Fit of Top Bed to Bottom Bed The bed post shall be designed so that the minimum height of lift to allow horizontal disengagement of the top bed from the bottom bed shall be 1 1/4 in. (32 mm), or a fastening mechanism may be used that will prevent the disengagement of the top bed from the bottom bed.	NA
4.3	Mattress and Foundation Size and Fit (Top Bed) There shall be no gaps between the interior bed structure and the edges of the mattress and foundation that will permit complete passage of the wedge block when tested in accordance with 5.2. 5.2 Mattress and Foundation Size and Fit (see 4.3)—Upper Foundation: 5.2.1 Place the intended mattress and foundation, as specified by the instructions, on the upper foundation support. 5.2.2 Move the mattress and foundation horizontally to obtain the largest gap between the interior bed structure and the edge of the mattress and foundation. 5.2.3 Insert the wedge block shown in Fig. 5, tapered side downwards, and in the most adverse orientation, into any gap and gradually apply a 45 lbf (200 N) vertically	P



Test Report

NUMBER : TSNH00565155

Clause	Testing Items / Requirements	Assessment
	<p>downwards force. Sustain the force for a period of 1 min.</p>  <p>FIG. 5 Wedge Block for Tests in Section 5</p>	
4.4	<p>Mattress Size and Fit (Lower Foundation)</p> <p>There shall be no space, between the edge of the manufacturer's recommended mattress and the interior boundary of any component(s) attached to lower bunk (for example, ladders, book shelves, desk), greater than 1.88 in. (48 mm) and smaller than 9 in. (229 mm), when tested in accordance with 5.3.</p> <p>5.3Mattress Size and Fit (see 4.4)—Lower Foundation: 5.3.1Place the intended mattress and foundation, as specified by the manufacturer, on the lower mattress support. 5.3.2For components attached to the side of the lower bed, and for which the mattress height is above the side rail, move the mattress horizontally to obtain the largest gap between the mattress and the interior boundary of any attached component. 5.3.3Determine if any space between the edge of the manufacturer's recommended mattress and the interior boundary of any attached component is between 1.88 in. (48 mm) and 9 in. (229 mm).</p>	NA
4.5	<p>Upper and Lower Foundation Support Systems</p>	--
4.5.1	<p>The foundation support systems shall confine the horizontal position of the mattress and the foundation and shall prohibit the mattress and foundation from falling when the mattress or foundation is manipulated.</p>	P
4.5.2	<p>In the event cross-members are utilized, a minimum of two per bed are required. If more than two cross-members are utilized, they shall be spaced so that the distance between adjacent cross-members or between the cross-members and the bed end structures will not permit complete passage of the wedge block or will allow complete passage of both the wedge block and a 9 in. (229 mm) diameter rigid sphere when tested in accordance with 5.9.</p> <p>5.9 Cross-Member Spacing— Place the wedge block shown in Fig. 5 into any opening</p>	P

Test Report

NUMBER : TSNH00565155

Clause	Testing Items / Requirements	Assessment
	tapered side first, and with the 3.5 in. dimension perpendicular to the cross-members. Determine if the wedge block cannot pass freely through the opening. If the wedge block can pass freely through the opening, the 9 in. (229 mm) diameter rigid sphere must pass freely through the opening. This requirement applies to both the upper and lower bunk foundation support systems.	
4.5.3	The foundation support system shall not be capable of being dislodged without the release of positive fastening devices or the use of hand tools.	P
4.5.4	The foundation support system shall not fail when tested in accordance with 5.4. 5.4 Foundation Support System (see 4.5)—Center a sheet of 3/4 in. (19 mm) thick plywood with dimensions 19 in. (483 mm) by 37 in. (940 mm) on the manufacturer's intended foundation (37 in. dimension parallel to the long axis of the bed), and place weights with a total mass of 400 lb (181.4 kg) on the plywood sheet. The weights shall be applied gradually and shall remain in place for a minimum of 5 min.	P
4.6	Side Rails	--
4.6.1	<i>Bolt-On Side Rails</i> , that attach at their ends or on their side to the bed post, shall be secured at each end by two bolts with a minimum size of 1/4 in. (6.4 mm) diameter or ISO/ANSI size M6. For wood beds, these bolts shall be spaced a minimum of 1 1/2 in. (38 mm) apart on their centers. When the bolts are fully tightened in the assembled bed, no more than 1/4 in. (6.4 mm) of thread shall be exposed.	P
4.6.2	<i>Hook-On Side Rails</i> , securely attached to the bed post. Hook-on attachments shall require an additional action other than an upwards force to disengage.	NA
4.6.3	Side Rail Attachments There shall be no structural failure of bed side rail fastening systems when tested in accordance with 5.5. 5.5 Side Rails (see 4.6)—Apply a downward vertical force of 225 lbf (1000 N) gradually, 10 in. from the bed end structure, and sustain it for 30 s. Apply the force sequentially to each corner of the bed.	P
4.7	Guardrails	--
4.7.1	Two guardrails shall accompany any bed in which the underside of the foundation is over 30 in. (762 mm) from the floor. Guardrails may be separate from or integral with the ladder.	P
4.7.2	Guardrails shall be attached in a manner that requires the intentional release of a fastening device or be so designed that they cannot be removed unless forces are applied sequentially in different directions.	P
4.7.3	The upper edge of the guardrails shall be at least 5 in. (127 mm) above the sleeping surface when a mattress of a thickness that is the maximum specified by the manufacturer's instructions is used on the bed.	P
4.7.4	With no mattress on the bed, there shall be no openings in the rigid bed structure below the lower edge of any opening of the guardrail that would permit complete passage of the wedge block when tested in accordance with 5.6. 5.6 Guardrails (see 4.7)—Place the wedge block shown in Fig. 5 into any opening in the rigid bed structure below the level of any opening of the guardrail, tapered side first, and in the most adverse orientation, and gradually apply a 33 lbf (148 N) force in a direction perpendicular to the plane of the opening. Sustain the force for a period of 1 min.	P
4.7.5	A guardrail may terminate before reaching the bed end structure, providing there is no more than 15 in. (381 mm) between either end of the guardrail and the bed end	P



Test Report

NUMBER : TSNH00565155

Clause	Testing Items / Requirements	Assessment
	structures in the same plane when measured at a point 5 in. (127 mm) above the sleeping surface as established by the maximum mattress thickness specified by the manufacturer. The second guardrail may terminate before reaching the bed end structure. If this guardrail terminates before reaching the bed end structure, there shall be no more than 0.22 in. (5.6 mm) between either end of the guardrail and the bed end structure when measured horizontally between the bed end structure and the nearest point on the guardrail.	
4.8	Bed Structure	--
4.8.1	The upper edge of the upper bunk end structures for at least 50 % of the distance between the two posts at the head and foot of the upper bunk shall be at least 5 in. (127 mm) above the sleeping surface when a mattress and foundation of the maximum size and thickness specified by the manufacturer's instructional literature is used on the upper bunk.	P
4.8.2	There shall be no openings in the rigid end structures of the upper bunk/bunks that will permit the free passage of the wedge block when tested in accordance with 5.7.1. This requirement shall apply only to those portions of the bed end structure that are above the foundation support system of the upper bunk/bunks. 5.7.1 Place the wedge block shown in Fig. 5 into any opening, tapered side first, and in the most adverse orientation. Determine if the wedge block can pass freely through the opening.	P
4.8.3	When tested in accordance with 5.7.2, there shall be no openings within the entire boundary of the lower bunk that will permit free passage of the wedge block, unless they are large enough to permit the free passage of a 9 in. (229 mm) diameter rigid sphere. This requirement does not apply to openings that are below the level of the lower bunk foundation support system. This requirement shall apply to that portion of the bed structure that is between the level of the lower bunk foundation support system and the level of the upper bunk foundation support system. Such openings include, but are not limited to, bed end structures, foundation, ladders, desks, or bookshelf components, or a combination thereof, as offered with the bed for purchase and designed to be attached to the bed structure. 5.7.2 Lower Bunk Boundaries (see 4.8.3): 5.7.2.1 Without a mattress or foundation on the lower bunk foundation support, place the wedge block shown in Fig. 5 into any opening, tapered side first, in the most adverse orientation. Determine if the wedge block can pass freely through the opening. If the wedge block passes freely through the opening, determine if a 9 in. (229 mm) diameter rigid sphere can pass freely through the opening. 5.7.2.2 With the manufacturer's recommended mattress and foundation size in place, on the lower bunk foundation support, repeat the test in 5.7.2.1.	NA
4.8.4	When tested in accordance with 5.7.2.3 and 5.7.2.4, all portions of the boundary of any opening of the entire lower bunk boundary that permits free passage of a 9 in. (229 mm) diameter rigid sphere also must conform to the neck entrapment requirement. 5.7.2.3 Insert the A section of the test template shown in Fig. 6 into the portion of the boundary of the opening to be tested, with the plane of the template in the plane of	NA



Test Report

NUMBER : TSNH00565155

Clause	Testing Items / Requirements	Assessment
	<p>the opening and with the centerline of the top of the template aligned parallel to the centerline of the opening, until motion is stopped by contact between the test template and the boundaries of the opening (see Fig. 7). By visual inspection, determine if there is simultaneous contact between the boundary of the opening and both sides of the A section of the template. If simultaneous contact occurs, mark the contact points on the boundary of the opening and conduct the additional test described in 5.7.2.4.</p> <p>5.7.2.4 Place the neck portion of the B section of the template into the opening, with its plane perpendicular to both the plane of the opening and the centerline of the opening (see Fig. 8). If the neck portion of the B section of the template completely enters the opening (passes 0.75 in. (19 mm) or more beyond the points previously contacted by the A section of the template), the opening fails the test, unless its lower boundary slopes downward at 45° or more for the whole distance from the narrowest part of the opening the neck can reach to the part of the opening that will freely pass a 9 in. (229 mm) diameter sphere.</p>	
4.9	Ladders	--
4.9.1	A lean-on (slanted) or hang-on (vertical) ladder shall be supplied with each bunk bed set or the ladder may be incorporated as part of the bed structure. The ladder may be separate from or integral with the guardrail. The ladder shall be attached in a manner that prevents inadvertent disengagement, repositioning, or tilting while in use.	P
4.9.2	There shall be no openings between ladder structures that allow complete passage of the wedge block, unless they are large enough to permit the free passage of the 9 in. (229 mm) diameter rigid sphere. The width of the ladder shall be no less than 10 in. (254 mm) measured from the inside of the stiles. Vertical spacing of ladder steps shall be no greater than 12 in. (305 mm) when measured from the floor to the first step or between steps. When bed structures are used as ladders, vertical spacing may be up to 16 in. (407 mm).	P
4.9.3	There shall be no openings between the ladder step and the upper bunk boundary that allow complete passage of the wedge block, unless they are large enough to permit the free passage of the 9 in. (229 mm) diameter rigid sphere.	P
4.9.4	<p>For ladders attached to the side of the lower bed and for which mattress height is above the side rail, there shall be no gaps between the edge of the manufacturers recommended mattress and the interior vertical stile between 1.88 in. (48 mm) and 9 in. (229 mm) when tested in accordance with 5.3.</p> <p>5.3 Mattress Size and Fit (see 4.4)—Lower Foundation: 5.3.1 Place the intended mattress and foundation, as specified by the manufacturer, on the lower mattress support. 5.3.2 For components attached to the side of the lower bed, and for which the mattress height is above the side rail, move the mattress horizontally to obtain the largest gap between the mattress and the interior boundary of any attached component. 5.3.3 Determine if any space between the edge of the manufacturer's recommended mattress and the interior boundary of any attached component is between 1.88 in. (48 mm) and 9 in. (229 mm).</p>	NA
4.10	Metal Beds: Frame and Fastenings	P
	There shall be no separation of any of the attachments of the foundation support system to the end structures of the bed when tested in accordance with 5.8.1.1 and 5.8.2.	



Test Report

NUMBER : TSNH00565155

Clause	Testing Items / Requirements	Assessment
	<p>5.8 Metal Beds—Frame and Fastenings:</p> <p>5.8.1 For testing in accordance with 5.8.1.1, the bed shall be prevented from sliding in a manner that does not prevent changes of angle that may take place in the bed structure.</p> <p>5.8.1.1 Position a test load of 165 lb (75.0 kg) at the center of the upper foundation support system on an area not to exceed 12 in. (305 mm) square (if foundation support systems will not permit the test load to be so positioned, it is permissible to add a platform to support the test load in such a way as to not increase the structural integrity of the bed). Apply an alternate force of 67 lbf (298 N) for 10 000 cycles at each point in the order ABCD or AB followed by CD at a rate not more than 24 loads per minute (see Fig. 9). The points for applying the test forces shall be located as near the center of the vertical bunk bed support as practicable at the height of the upper foundation support system.</p> <p>5.8.2 After testing in accordance with 5.8.1.1, remove the 165 lb (75.0 kg) load and apply a 67 lbf (298 N) force in directions most likely to cause separation between the end structure and foundation support system. The force shall be applied at each point of attachment of the foundation support system to the end structure (point of applications shall be as close as practical to the point of attachment). The force shall be applied to either the end structure or foundation support system, whichever appears most likely to cause separation.</p>	
5	Test Methods	--
6	Marking and Labeling	P (SEE REMARK)
7	Instructional Literature	P (SEE REMARK)

Abbreviation: P = Pass; NA = Not Applicable

Remark:

Only artwork was provided for evaluation.

To be continued



Test Report

NUMBER : TSNH00565155

2. 16 CFR Part 1513-Requirements for Bunk Beds Intended for Use by Children/16 CFR Part 1213-Requirements for Bunk Beds Not Intended for Use by Children

With reference to 16 CFR Part 1513 - Requirements for Bunk Beds & 16 CFR Part 1213 - Safety Standard for Entrapment Hazards in Bunk Beds.

Executive summary:

Clause	Requirements	Assessment
1513.3(a)/1 21 3.3(a)	Guardrails	--
(1)	Any bunk bed shall provide at least two guardrails, at least one on each side of the bed, for each bed having the underside of its foundation more than 30 inches (760 mm) from the floor.	P
(2)	One guardrail shall be continuous between each of the bed's end structures. "Continuous" means that any gap between the guardrail and end structure shall not exceed 0.22 inches (5.6 mm) (so as to not cause a finger entrapment hazard for a child).	P
(3)	The other guardrail may terminate before reaching the bed's end structures, providing there is no more than 15 inches (380 mm) between either end of the guardrail and the nearest bed end structures.	P
(4)	For bunk beds designed to have a ladder attached to one side of the bed, the continuous guardrail shall be on the other side of the bed.	P
(5)	Guardrails shall be attached so that they cannot be removed without either intentionally releasing a fastening device or applying forces sequentially in different directions.	P
(6)	The upper edge of the guardrails shall be no less than 5 inches (130 mm) above the top surface of the mattress when a mattress of the maximum thickness specified by the bed manufacturer's instructions is on the bed. This requirement does not prohibit a wall-side guardrail that terminates in a quarter-circle bend and attaches to the side rail of the upper bunk foundation.	P
(7)	With no mattress on the bed, there shall be no openings in the structure between the lower edge of the uppermost member of the guardrail and the underside of the upper bunk's foundation that would permit passage of the wedge block shown in Figure 1 of this part when tested in accordance with the procedure at §1513.4(a)/1213.4(a).	P



Test Report

NUMBER : TSNH00565155

Clause	Requirements	Assessment
1513.3(b)/1 21 3.3(b)	Bed end structures	--
(1)	The upper edge of the upper bunk end structures shall be at least 5 inches (130 mm) above the top surface of the mattress for at least 50 percent of the distance between the two posts at the head and foot of the upper bunk when a mattress and foundation of the maximum thickness specified by the manufacturer's instructions is on the bed.	P
(2)	With no mattress on the bed, there shall be no openings in the end structures above the foundation of the upper bunk that will permit the free passage of the wedge block shown in Figure 1 when tested in accordance with the procedure at §1513.4(b)/1213.4(b).	P
(3)	When tested in accordance with §1513.4(c)/1213.4(c), there shall be no openings in the end structures between the underside of the foundation of the upper bunk and upper side of the foundation of the lower bunk that will permit the free passage of the wedge block shown in Figure 1, unless the openings are also large enough to permit the free passage of a 9-inch (230-mm) diameter rigid sphere.	NA
(4)	All portions of the boundary of any opening required by §1513.4(c)(1) and (2)/1213.4(c)(1) and (2) to be probed by the wedge block of Figure 1, and that permits free passage of a 9-inch diameter sphere, must conform to the neck entrapment requirements of §1513.4(c)(3)/1213.4(c)(3).	P
1513.5/1213 .5	Marking and labeling	P (SEE REMARK)
1513.6/1213 .6	Instructions	P (SEE REMARK)

Abbreviation: P = Pass; NA = Not Applicable

Remark:

Only artwork was provided for evaluation.

To be continued



Test Report

NUMBER : TSNH00565155

3. Tracking Label Assessment

As per consumer product safety Act section 14(a) (5), 15 U.S.C. §2063(a)(5) (CPSA) and Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels for Children Products

Tracking label found on the packaging:

Compliance Information-Not Retailer
Shenzhen Yuefeng Zhiqi Technology Co., Ltd
A708-E1, 7th Floor, Block A, Building A, Jiangsu Building,
No. 6013 Yitian Road, Fuxin Community, Lianhua Street,
Futian District, Shenzhen 518000
Made in Hebei, China
07/2025
P.O.NO:USO01MINGYANG20250710
W00327AAB

Tracking label found on the product:

Compliance Information-Not Retailer
Shenzhen Yuefeng Zhiqi Technology Co., Ltd
A708-E1, 7th Floor, Block A, Building A, Jiangsu Building,
No. 6013 Yitian Road, Fuxin Community, Lianhua Street,
Futian District, Shenzhen 518000
Made in Hebei, China
07/2025
P.O.NO:USO01MINGYANG20250710
W00327AAB

Name of importer	Shenzhen Yuefeng Zhiqi Technology Co., Ltd
Location of production	Hebei, China
Date code	07/2025

Note: The tracking label assessment was based on the submitted sample and the information provided by the applicant. There was no verification on the validity of such information.

Remark:

Only artwork was provided for evaluation.

To be continued



Test Report

NUMBER : TSNH00565155

4. Physical and Mechanical Tests

As per U.S. Code of Federal Regulations Title 16 part 1500.50, the hazards of sharp points, sharp edge and small parts are assessed both before and after applicable use and abuse tests.

Appropriate age group for testing : 3+

	No. of sample tested	Sharp Point <u>(1500.48)</u>	Sharp Edge <u>(1500.49)</u>	Small Part <u>(1501)</u>
As received	1	P	P	NA
Impact test (1500.53(b))	1	P	P	NA
Flexure test (1500.53(d))	0	NA	NA	NA
Torque test (1500.53(e))	1	P	P	NA
Tension test (1500.53(f))	1	P	P	NA
Compression test (1500.53(g))	1	P	P	NA

Remark: P = Pass NA = Not Applicable

5. Flammability test

As per U.S. Code of Federal Regulations Title 16 Part 1500.44 for rigid and pliable solids

Result : Did not ignite

To be continued



Test Report

NUMBER : TSNH00565155

6. Total Lead (Pb) Content in Surface Coating

As per standard operating procedure for determining Lead (Pb) in paint and other similar surface coatings (April 26, 2009), test method CPSC-CH-E1003-09.1 was used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

<u>Tested Components</u>	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
(1&6)	<20	90

The limit was quoted according to U.S. Consumer Product Safety Improvement Act 2008 title I, section 101 for total Lead content in surface coating.

Remark: ppm = Parts per million based on dry weight of sample = mg/kg
< = Less than

Tested Components:

- (1) Black coating on frame for sample use
- (6) White coating on frame for sample use

7. Total Lead (Pb) Content In Non-Surface Coating Materials (Substrate)

As per standard operating procedures for determining total Lead (Pb) in children's products, test method(s) CPSC-CH-E1002-08.3 and CPSC-CH-E1001-08.3 were used and total Lead content was determined by Inductively Coupled Argon Plasma Spectrometry.

<u>Tested Components</u>	<u>Result (ppm)</u>	<u>Limit (ppm)</u>
(2&3)	35	100
(4&5)	36	100
(7&8)	18	100

Remark: ppm = Parts per million = mg/kg

Tested Components:

- (2) Black metal big screw on frame for sample use
- (3) Black metal small screw on frame for sample use
- (4) Silver color metal big screw on frame for sample use
- (5) Metal substrate of frame for sample use
- (7) Black plastic cap on square tube for sample use
- (8) White plastic cap on square tube for sample use

To be continued



Test Report

NUMBER : TSNH00565155

8. Phthalate Content

According to CPSC-CH-C1001-09.4, by Gas Chromatographic-Mass Spectrometric (GC-MS) analysis.

<u>Test item</u>	<u>Result (%)</u>		<u>Limit (%) (Max.)</u>
	(1&6)	(7&8)	
Dibutyl phthalate (DBP)	ND	ND	0.1
Di-(2-ethylhexyl) phthalate (DEHP)	ND	ND	0.1
Benzyl butyl phthalate (BBP)	ND	ND	0.1
Diisononyl phthalate (DINP)	ND	ND	0.1
Diisobutyl phthalate (DIBP)	ND	ND	0.1
Di-n-pentyl phthalate (DPENP)	ND	ND	0.1
Di-n-hexyl phthalate (DHEXP)	ND	ND	0.1
Dicyclohexyl phthalate (DCHP)	ND	ND	0.1

The above limit was quoted according to 16 CFR part 1307 approved by U.S. Consumer Product Safety Commission (CPSC) for prohibition of children's toys and child care articles containing specified phthalates.

Remark: ND = Not Detected
Detection Limit = 0.01%

Tested Components:

- (1) Black coating on frame for sample use
- (6) White coating on frame for sample use
- (7) Black plastic cap on square tube for sample use
- (8) White plastic cap on square tube for sample use

Date sample received: Oct 11, 2025

Testing period: Oct 11, 2025 to Oct 21, 2025


To be continued

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.



Test Report

NUMBER : TSNH00565155



Instructions

Compliance Information-Not Retailer
 Shenzhen Yuefeng Zhiqi Technology Co., Ltd
 A708-E1, 7th Floor, Block A, Building A, Jiangsu Building,
 No. 6013 Yitian Road, Fuxin Community, Lianhua Street,
 Futian District, Shenzhen 518000
 Made in Hebei, China
 07/2025
 P.O.NO:USO01MINGYANG20250710
 W00327AAB

Tracking label



WARNING 4.8MM

To help prevent serious or fatal injuries from entrapment or falls:

- Never allow a child under 6 years on upper bunk.
- Use only a mattress that is 79"-80" long and 38"-39" wide on upper bunk. 3.2MM
- Ensure thickness of mattress and foundation combined does not exceed 6" and that mattress surface is at least 5" below upper edge of guardrails.
- Use guardrails on both sides of upper bunk.
- Prohibit horseplay on or under bed(s).
- Prohibit more than one person on upper bunk.
- Use ladder for entering and leaving upper bunk.
- **STRANGULATION HAZARD**- Never attach or hang items to any part of the bunk bed that are not designed for use with the bed; for example, but not limited to, hooks, belts, and jump ropes.

DO NOT REMOVE THIS LABEL 4.8MM

Warning label

End of report

