


LED Oval Mirror

Size: 780*1300*35MM



Mirror with Magnifyer and Anti-Fog

Installation • Operation • Safety • Warranty



Magnifying
Side Mirror



Dual Touch Button with
Dimming Function




Smart Defogger
Function

LED Oval Mirror

Mirror with Magnifyer and Anti-Fog

Size: 780*1300*35MM

PRODUCT FEATURES



- LED Oval Mirror
- Stainless Steel Frame
- Anti fog function
- Dimming function
- Magnifying Mirror on the left
- 2 key touch sensor switch

LED Oval Mirror

Mirror with Magnifyer and Anti-Fog

Size: 780*1300*35MM

QUICK START

1. Turn OFF power at the breaker (verify with tester).
2. Locate studs and mark centerline
3. Install hanging bar/brackets level.
4. Make hard-wired electrical connections.
5. Hang mirror; lock-catch for horizontal mount.
6. Restore power; test touch sensors (light, anti-fog).

SAFETY & COMPLIANCE

- Installation by a licensed electrician only.
- Connect to a GFCI-protected, properly grounded circuit (120 V~ 60 Hz).
- Do not connect to any wall dimmer (ELV/triac). Use a standard ON/OFF switch if desired; dimming happens on the mirror.
- Two-person lift required; use PPE.
- Mount into wall studs whenever possible; use proper anchors for wall type.



DANGER



GFCI Protected



No wall dimmer



Ground properly



Two-person lift



PPE

LED Oval Mirror

Mirror with Magnifier and Anti-Fog

Size: 780*1300*35MM

WHAT'S IN THE BOX & TOOLS

INCLUDED



Mirror
assembly



Hanging
bar



Wall
screws
(x2)



Anchors
(x2)

TOOLS NEEDED



Band
tap



Level



Pencil



PPE



Drill
bits



Electronic
drill



Cross
screwdriver



Stud
finder

LED Oval Mirror

Mirror with Magnifyer and Anti-Fog

Size: 780*1300*35MM

HARDWIRE INSTRUCTIONS

Warning: Manufacturer's warranty shall be void if product is not installed by a licensed professional

Prior to commencing installation, please ensure the following:

- The wall where the product is being installed is able to support the weight of the product
- The main electrical supply has been powered off to complete installation

IMPORTANT: Wiring Instructions for Canada & USA



This fixture's wiring colors may not align with standard North American guidelines. For a safe installation, please re-identify the fixture wires with electrical tape as follows:

LIVE: Wrap black tape on the fixture's White wire. Connect this to your home's Black (Live) wire.

NEUTRAL: Wrap white tape on the fixture's Black wire. Connect this to your home's White (Neutral) wire.

GROUND: Connect the Green wire to your home's Green or Bare Copper ground wire.

Please consult a licensed electrician if you are unsure.



Important


- Hard-wire only. Do not attach a cord-and-plug.
- Use listed wire connectors; make all splices inside approved boxes.
- Do not use a wall dimmer. Use a standard ON/OFF switch if wall control is required.

LED Oval Mirror

Mirror with Magnifyer and Anti-Fog

Size: 780*1300*35MM

WALL MOUNTING INSTRUCTIONS




Measure the distance of the mounting hole.
Drill holes with a suitable sized drill.



Insert the anchor and mounting screw into the wall.



Connect the mirror wires with your main wires and hang the mounting hole to the screw on the wall.




Peel off protective film and clean the mirror with damp cloth.

LED Oval Mirror

Mirror with Magnifier and Anti-Fog


Size: 780*1300*35MM

OPERATION & FEATURES



MIRROR LIGHT USE


Short touch the left sensor to turn on / off the mirror light.



MIRROR DIMMING LIGHT USE

Long touch the left sensor to dimming the mirror light.

15%, 50%, and 100% dimming levels.



MIRROR DEFOGGING USE

Short touch the right sensor to turn on / off the mirror defogging function.

LED Oval Mirror

Mirror with Magnifyer and Anti-Fog

Size: 780*1300*35MM

CARE & CLEANING AND TROUBLESHOOTING

CARE & CLEANING



Wipe with a soft, lint-free cloth; mild non-ammonia cleaner.



Do not use abrasives, pads, acids, or solvents.



Apply cleaner to cloth, not directly on sensor areas.

TROUBLESHOOTING (QUICK FIXES)



No light at install: Confirm breaker ON, correct wiring, internal quick-connects fully seated.



Touch unresponsive: Power cycle at breaker for 60 seconds; clean/dry glass over sensors.



Buzz/Hum: Ensure unit is not on a wall dimmer; verify solid ground.



Anti-fog not warming: Ensure left sensor is ON; feature auto-turns-off after 1 hour.