Project / Job Name:

Location:

Fixture Type:

Notes:

**S30110** - LED Compact Multi-Light; 1200 Max Lumens; USB-C Rechargeable; 3.7 Volt; 12pc Tray Pack

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 6.25 |
| EA Width | 3.5 |
| EA Length | 1.0 |
| Material | Aluminum |
| Fixture Type | Rechargeable Task |
| Includes | USB-A to USB-C Charging Cable |
| Product Notes | Integrated Rechargeable 3.7V Li-ion Battery; Charge Time: 3HRS |
| Status | Active |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | Black |
| Additional Info | Ships in retail-ready display trays and packaging |
| Integrated Features | Magnetic Base; Hang Hook; Pocket Clip; Strobe |
| Lens Finish | Clear |
| Lens Material | Acrylic |
| Lensed | Yes |
| Portable Light Modes | Emergency Strobe, High, Low, Medium, Turbo |
| Product Technology | LED |
| Serviceable Battery | No |
| Beam Distance (Ft) | 361 |
| Battery Indicator | No |
| Digital Display | No |
| Drop Impact Rating | 3.28 Ft (1M) |
| Battery Operating Temp | +32F to +104F (0C to +40C) |
| Light Source Quantity | Double |
| Power Bank Storage | 2000mAh |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 6500K |
| Dimmable | Yes-Dimmable |
| Color Temp | Daylight |
| CRI | 50+ |
| Dimming Type | Only dimmable via setting selection, Step Dimming |
| Operating Temp | +32F to +104F (0C to +40C) |
| Lumens | 1200L/500L/250L/100L/400L/200L/100L |
| Volts | 3.7V |
| Max Lumens | 1200L |
| Connection | USB-C Rechargeable |
| Charge Time | 3hr |
| Battery Chemistry | LiFePO4 |
| Replaceable Battery Type | 103450 |
| USB Type In | 1 USB-C |

## PHYSICAL

| | |
|---|---|
| Finish | Black / Red |
| Housing Color | BlackRed |
| Mounting Procedure | Belt Clip, Hang Hook, Magnetic Base, Tripod Mount |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 1-Year |
| Installation Notes | Do Not Charge The Product Below 40F Or above 104F; Do Not Exceed 5V DC, 0.8A Charging |
| Portable Light Functions | LED Spot Function, Red Light Function, White Light Function |

## PACKAGING

| | |
|---|---|
| UPC | 045923300110 |
| Case Cube | 0.7028 |
| Case Height | 9.25 |
| Case Length | 8.66 |
| Case Quantity | 24 |
| Case UPC | 10045923300117 |
| Case Weight | 9.34 |
| Case Width | 15.16 |
| EA Cube | 0.0127 |
| EA Height | 6.25 |
| EA Length | 1.0 |
| EA Quantity | 1 |
| EA Weight | 0.28 |
| EA Width | 3.5 |
| Inner Cube | 0.2169 |
| Inner Height | 7.44 |
| Inner Length | 6.77 |
| Inner Quantity | 12 |
| Inner UPC | 20045923300114 |
| Inner Weight | 4.18 |
| Inner Width | 7.44 |
| Pack Type | Color Box |
| Web Height | 4.33 |
| Web Length | 0.79 |
| Web Width | 1.85 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IP Rating | IPX4 |
| ROHS Compliant | Yes |
| Energy Star Certified | No |
| T24/JA8 Compliant | No |
| Performance Standards | ANSI PLATO FL1 |



© Satco Products, Inc.
All rights reserved 2026