



## Installation Steps:

Thank you for using our products. Please read the operation manual before installation. Please keep this operation manual as a reference. Disconnect the power supply before installing this product. Installation by a professional electrician is recommended.

1. Remove the cylindrical nut on the top of the light fixture, then use the wrench to fix the light arm firmly in turn, and finally cover the lid to torque the cylindrical nut.
2. Fix the iron pipe to the lamp body with the knob in turn, and it is better to connect it to the disk on the ceiling.
3. Fix the hanging plate to the reserved mounting box.
4. Connect the black wire to the black power cord with a wire cap (supplied), connect the white wire to the white power cord and wrap tightly with insulating tape. Connect the ground wire of the fixture to the ground wire of the junction box. If the house does not have a ground wire, connect it to the green screw on the wall plate (the screw labeled GND). (screw labeled GND).
5. Secure the light to the wall plate with the round head nut.
6. Attach the bulb to the lamp head, ensuring good contact.

## Attention:

1. The input power of the lamp is AC 120V 50Hz.
2. Any behavior that violates residential fire protection regulations is prohibited.
3. Under no circumstances should the lamps be covered with heat insulation pads or wooden materials.
4. Before maintenance, make sure that the power supply of the lamp has been cut off and the light source has cooled down. Before powering on, make sure that the light source and the lamp holder are connected correctly.
5. Please wipe with a towel or flannel, and clean the lamp body with a non-corrosive detergent. Do not scrub directly, wipe with water or a damp cloth.
6. If you have any questions about this manual, please consult a qualified lighting installation engineer.