

NEW!**DURHAM[®]**
MANUFACTURING

Flammable Safety Cabinets



Part Number Manual Closing	Capacity Gallons (L)	Dimensions W x D x H - In (mm)	Shelves	Door Style	Ship Wt.
1012M-50	12 (45)	23" x 18" x 35" (584 x 457 x 889)	1	Manual	135 lbs.
1012S-50	12 (45)	23" x 18" x 36-3/8" (584 x 457 x 924)	1	Self Closing	140 lbs.
1030M-50	30 (114)	43" x 18" x 44" (1092 x 457 x 1118)	1	Manual	250 lbs.
1030S-50	30 (114)	43" x 18" x 45-3/8" (1092 x 457 x 1153)	1	Self Closing	255 lbs.
1045M-50	45 (170)	43" x 18" x 65" (1092 x 457 x 1651)	2	Manual	315 lbs.
1045S-50	45 (170)	43" x 18" x 66-3/8" (1092 x 457 x 1686)	2	Self Closing	320 lbs.
1060M-50	60 (227)	34" x 34" x 65" (834 x 864 x 1651)	2	Manual	325 lbs.
1060S-50	60 (227)	34" x 34" x 66-3/8" (834 x 864 x 1686)	2	Self Closing	330 lbs.
1090M-50	90 (340)	43" x 34" x 65" (1092 x 864 x 1651)	2	Manual	355 lbs.
1090S-50	90 (340)	43" x 34" x 66-3/8" (1092 x 864 x 1686)	2	Self Closing	360 lbs.

Flammable Safety Cabinet

- Sturdy all welded double wall steel construction
- 10 cabinets - 5 manual closing, 5 self closing
- 60 & 90 gallon models have internal 16 gauge reinforcements
- 2" wide louvers support shelves, adjustable on 4" centers
- 2" Deep leak proof sump
- Safely contains hazardous chemicals, reducing the risk of fire
- Improved security with recessed lockable paddle latch and 3 point locking system
- 2" Bunged air vents with flame arrestors on each side of the cabinet allows for ventilation
- Safety yellow powder coat finish



Applications

Cabinets are required by OSHA and UFC in commercial and industrial facilities where flammable liquids are used and stored. Units conform to NFPA code 30 and OSHA 29 CFR 1910.106 and are FM approved.



Phone: 860.349.3427 - Fax: 860.349.8235
www.durhammfg.com - info@durhammfg.com

Safety Storage Cabinets



First Aid



Gas Cylinder Storage



Manufacturing Safety Products Since 1922