



sok® | K-1189-RE

63" x 31-1/2" drop-in Effervescence bath with left-hand drain

Features

- Built-in heater
- Remote control
- Overflow channel for deep soak and unique infinity pool effect



Available Colors/Finishes

Color tiles intended for reference only.

0 White



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-30-2026 01:24 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

ASME A112.19.7/CSA B45.10
CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
UL 1795
CSA C22.2 No. 218.2
cUL Listed
UL Listed

Technical Information

All product dimensions are nominal.

Drain Location:	Left
Drain Hole Diameter:	2-1/4" (57 mm)
Basin Area, Bottom:	45" x 25-1/2" (1143 mm x 648 mm)
Basin Area, Top:	61-1/2" x 30-1/4" (1562 mm x 768 mm)
Water Depth:	23-1/2" (597 mm)
Water Capacity:	142 gal (537.5 L)
Minimum Floor Load:	59 lbs/ft ²
Weight:	277 lbs (125.6 kg)
Cutout:	Drop-in, 73-1/2" x 39-1/2" (1867 mm x 1003 mm)

Material

- Acrylic

Recommended Products/Accessories

K-1601 Bath/whirlpool footstop, removable
K-23726 Drain treatment
K-23732 Tub & shower cleaner
K-923 Wall- or -ceiling-mount bath filler

Required Products/Accessories

- K-7193 Drain for overflowing bath

Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump: 240 V, 20 A, 50/60 Hz

Heater: 240 V, 20 A, 50/60 Hz

Electrical Component Ratings

Pump: 240 V, 17 A, 50/60 Hz

Number of Speeds: Variable


Heater: 240 V, 17 A, 50/60 Hz, 4000 W

Warranty

See website for detailed warranty information.

KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty|KOHLER® Hydrotherapy Components Five-Year Limited Warranty





Installation

- Drop-in

Installation Notes

Install this product according to the installation instructions.

Measure your actual product for rough-in details.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Consult local and national codes for minimum air gap requirements when installing a spout on the faucet deck.

Unit must be filled through the bathing well.



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-30-2026 01:24 - US-CA