

Vessel Sink Assembly Guide

This guide explains how to assemble and install a 14-inch round brass lacquered vessel sink. Dimensions: 14" diameter (≈355 mm), 5" height (≈127 mm). Drain opening: 45 mm standard. A compatible drain is included.

Specifications

Feature	Imperial	Metric
Diameter	14"	355 mm
Height	5"	127 mm
Drain Opening	≈1.77" (Standard)	45 mm

Simple Reference Drawing (Not to Scale)

Diameter: 14" (355 mm) _____ / \ | | <- 5" (127 mm) height \ _____ / Drain
Opening: 45 mm centered

Included Parts

- 1x Brass lacquered vessel sink (14" x 5")
- 1x Standard 45 mm drain assembly
- 1x Rubber gasket
- 1x Locking nut
- 1x Optional plumber's putty or silicone (not included)

Installation Steps

1. Place the countertop in position and ensure the drain hole aligns with the sink's drain opening.
2. Insert the included rubber gasket under the sink base if needed, depending on counter material.
3. Position the vessel sink over the drain hole.
4. Insert the drain body through the sink and countertop.
5. From underneath, install the gasket and locking nut onto the drain body.
6. Tighten the locking nut by hand, then secure slightly using pliers (do not overtighten).
7. Apply a thin bead of silicone around the base if additional sealing is preferred.
8. Connect the drain to the plumbing trap according to local US plumbing code.

9. Run water to check for leaks; tighten connections if required.

Maintenance Tips

- Clean with mild soap and soft cloth only.
- Avoid abrasive cleaners to protect the lacquer finish.
- Check drain connections periodically for tightness.