



▲ Designate proper finish suffix



see what Delta can do™

HAND SHOWER

■ 2-Spray Setting Hand Shower

FEATURES:

- Touch-Clean® Spray Holes

STANDARD SPECIFICATIONS:

- Max flow rate 1.5 gpm @ 80 psi, 5.7 L/min @ 550 kPa (59462-▲B15-BG)
- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa (59462-▲B18-PK)
- Max flow rate 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (59462-▲B-PK)
- Certified dual check valves for backflow protection
- ADA compliant hand shower when installed per accessibility guidelines of the act
- Pause flow by pressing the button on the handle - pause is a non-positive shut-off
- 2 Spray settings include: Full Body spray and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1◆
- ASME A112.18.3◆
- EPA WaterSense® - Applies to 59462-▲B15-BG and 59462-▲B18-PK only
- ♿ ICC/ANSI A117.1

- ◆ Your Delta hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company