Project:

Fixture Type: Location:

Contact:

Ceiling mounted • Damp location listed

Images:



LED

Featuring a sleek and slim appearance, the 160in. flush mount is an architectural flush mount. Etched white glass is accented by a metal trim in a Polished Chrome finish. The glass shade is illuminated on both the bottom and sides to provide a pleasing lighted effect.

#### **Specifications:**

- Polished Chrome (plated) •
- Steel Construction
- Etched White glass Bowl .
- . Features a sleek and slim appearance inspired by architectural design
- The glass shade is illuminated on both the bottom and sides to provide a pleasing lighted effect
- · Fits seamlessly within Modern, Traditional and Transitional interiors
- Polished Chrome finish
- Measured 16in diameter x 4-3/4in ht.
- Contains one 26W LED Module 1,142 delivered lumens 44 lumens/watt, 3000K color tempera-. ture, 90+ CRI.
- · CSA Safety listed for use in damp locations
- Compatible with many ELV dimmers •
- These products are designed for exceptional quality, reliability, and functionality .
- · Includes installation instructions and mounting hardware
- Dimmable to 10% brightness (See Dimming Notes) .
- Fixture covers a standard 4" octagonal recessed outlet box •
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified Meets California Title 24 JA8-2016

# •

### **Performance:**

Number of Modules	1	
Input Power	26w	C V
Input Voltage	120 V	ŀ
Input Frequency	60 Hz	
Lumens/LPW (Source)	1770/68.07692307692308 (LM-82)	
Lumens/LPW (Delivered)	1142/43.7 (LM-79)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	50,000 (L70/TM-21)	
FCC	FCC Title 47, Part 15, Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30°C	
Warranty	5-year limited warranty	
Labels	cCSAus Damp location listed	
	ENERGY STAR <sup>®</sup> qualified	
	Meets California Title 24 JA8-2016	





### **Dimensions:**

Diameter: 16" Height: 4-3/4"

lass 'idth: 15-5/16" eight: 3-13/16" LED



# **Dimming Notes:**

This Led is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Lutron - NTEVL-300		
Lutron - DVELV-300P		
Lutron - Caseta Wireless		
Leviton – 6672		
Leviton — 6674		
Lutron - AYCL-153P		
Lutron - AYLV-600P		
Lutron - MAELV-601		
Leviton - AWRMG-EAW		

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.