

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Thread the tubes one by one onto the nipple, then thread swivel into the tube tightly.
2. Thread 2 mounting screws properly into the 2 relevant mounting holes pre-drilled on the cross bar.
3. Attach the cross bar to outlet box using 2 outlet box screws upwards.
4. Weave fixture wires and ground wire through the every tube, swivel and canopy.
5. Make wire connections:
 - Attach ground wire to house ground wire using a wire nut or attach them to the cross bar with a green ground screw.
 - Attach white wire from light to white wire from power source with a wire nut.
 - Attach black wire from light to black wire from power source with a wire nut.

Observing: positive wire with positive wire, negative wire with negative wire, ground wire with ground wire.
6. Tuck the wire connections neatly into the outlet box.
7. Attach the canopy to the ceiling and let the two mounting screws protrude through the two pre-drilled keyholes on the canopy, then fix it in place by ball nuts.
8. Install bulb. (not included)(Please do not exceed the maximum capacity which is recommended on the fixture.)
9. Place the glass panel in the center of the metal frame and then rotate the metal clip toward inside to clip the glass panel. Secure the screw A onto the diffuser tab. Attach the metal ring onto the metal frame. Use the screw B to fix it onto the metal frame. The bottom diffuser with ring is finished. Finally, secure the bottom diffuser with ring to the metal shade by finial.
10. Turn on the power at fuse or circuit box.

