



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11560 - 9 Watt; LED Direct Wire; Low Profile Downlight; 4 Inch Round; Starfish IOT; Tunable White and RGB; 120 Volt; 90 CRI; White Finish

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V
Lumens:	540L
CRI:	90
CCT (Kelvins):	2000K-5000K
Color Description:	Warm to Cool White/Color Changeable
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
DimmableText:	Only with Starfish App
Dimming Type :	Smart-Starfish App only
Incandescent Equivalent :	45W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Direct Wired
THD:	<30%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923115608
Each Quantity:	1
Each Dimensions:	5.78 x 3.35 x 5.31
Inner UPC:	20045923115602
Inner Quantity:	0
Inner Dimensions:	0.00 x 0.00 x 0.00
Case UPC:	10045923115605
Case Quantity:	20
Case Dimensions:	17.52 x 12.00 x 11.00

INFO

Installation Note:	Driver Dimensions: 3.46 Inches Long x 3.46 Inches Wide x 1.44 Inches High
--------------------	---

PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	H:1.00" DIA:5.00"
Weight (Lbs.):	0.88
Material:	Aluminum

INSTALLATION

Max Drywall Thickness:	1 in.
------------------------	-------

IOT

IOT Enabled:	Yes
What's Supported:	Google Home;Alexa;Siri;SmartThings

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2494955
Energy Star Lamp Category:	Downlight Recessed
UL/ETL Standard:	ANSI/UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

ACCESSORIES

**80-943**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter

**80-946**4" Goof Ring for Remote Driver Installation

**80-950**New Construction Mounting Plate for Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter

**80-986**6 Foot Remote Driver Extension Cable; 2-Pin; White Finish
