

ASSEMBLY INSTRUCTION

Congratulations:

You purchased one of the best lighting product available in the market.

In order to ensure safety and maximize the life time of the lamp, please make sure to read following precautions and instructions thoroughly before assembling your lamp.

Assembly Instructions:

Note: The electrical wire is connected continuously through the poles.

Please DO NOT pull wire during unpacking. Bad connections may result.

For easier installation, two people are recommended for the installation process.

1. Carefully unpack all parts from packing and lay flat on carpet.
2. Screw Steel Pipe (D) on to Base (E) tightly.
3. Screw Steel Pipe (C) on to Steel Pipe (D), tighten and push down excess wire into Steel Pipe (C).
4. Screw Steel Ball Part (H) on to Metal Shade (A), tighten and puch down excess wire into Steel Pipe (B).
5. Screw Steel Pipe (B) on to Steel Pipe (C).
6. Connect the Female (F) and Male Connector (G), plug in any outlet, your lamp is ready to use.

Resetting the Automatic Tilt-Off Switch:

Please note: Tilt-off switch works best on flat/hard surface.

1. Plug the lamp into an outlet to test whether the lamp is working properly.
2. If there is no light coming out when the switch is on, reset the Automatic Tilt -Off switch located at the bottom of the Base by pushing the switch inward and release it, or just lift the lamp a few inches from the ground and put down, (you just reset the tilt-off switch) and now your lamp is ready to use again.

WARNING:

Do not polishes or cleaners on your lamp.

JUST WIPE CLEAN WITH SOFT CLOTH.

