

Examine all packaging material for small parts that may have come loose during shipment. Periodic checks are recommended to insure that all components are in proper position, tight and free from damage. Keep this assembly instruction for future reference. Adult assembly is required. The product of Hillsdale Furniture, LLC is designed for residential use only. Customer Service Phone Number: 502-562-0000


HDFBP

HARDWARE LIST

- A (14) 1/4" x 15mm Allen Bolts
B (2) 1/4" x 20mm Allen Bolts
C (4) 1/4" x 25mm Allen Bolts
D (20) 1/4" Spring Washers
E (20) 1/4" Flat Washers
F (1) 1/4" Allen Wrench

PARTS LIST

- G (1) Stool Back
H (1) Seat
I (1) Top Ring
J (4) Stool Legs
K (1) Support Ring

PART	QTY	HARDWARE	PART	QTY	HARDWARE
A	14		B	2	
C	4		D	20	
E	20		F	1	

STEP 1

Begin assembly by attaching the Stool Back (G) to Seat (H) by inserting each post in place and securing from the inside with 1 Allen Bolt (A), 1 Spring Washer (D) & 1 Flat Washer (E) per each post. Do not fully tighten bolts for this step.

STEP 2

Once in place, also secure Stool Back (G) from the bottom of Seat (H) using 1 Allen Bolt (B), 1 Spring Washer (D) & 1 Flat Washer (E) per each post. Tighten all bolts from Steps 1 and 2.

STEP 3

Next attach each Stool Leg (J) to the bottom of Top Ring (I) by aligning holes and securing with 2 Allen Bolts (A), 2 Spring Washers (D) & 2 Flat Washers (E) per each leg. Do not fully tighten bolts for this step.

STEP 4

Attach Support Ring (K) to the inside of each Stool Leg (J) by fitting in place over the metal tabs and securing with 4 Allen Bolts (A), 4 Spring Washers (D) & 4 Flat Washers (E). Tighten all bolts.

STEP 5

Finally attach Seat (H) to Top Ring (I) by aligning the holes with the swivel metal plate and secure with 4 Allen Bolts (C), 4 Spring Washers (D) & 4 Flat Washers (E). The assembly is now complete.

