



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11295** - 15 Watt; LED Gimbaled Downlight; 6 Inch; RGB & Tunable White; Round; Starfish IOT; White Finish; 1200 Lumens; 120-277 Volt

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



## ELECTRICAL

|                            |                                     |
|----------------------------|-------------------------------------|
| Technology:                | LED                                 |
| Watts:                     | 15W                                 |
| Volts:                     | 120V-277V                           |
| Lumens:                    | 1200L                               |
| CRI:                       | 90                                  |
| CCT (Kelvins):             | 2700K-5000K                         |
| Color Description:         | Warm to Cool White/Color Changeable |
| Beam Spread :              | 36                                  |
| Hours Rated:               | 50000                               |
| Dimmable:                  | Yes-Dimmable                        |
| DimmableText:              | Only with Starfish App              |
| Incandescent Equivalent :  | 75W                                 |
| Operating Temperature :    | -20C (-4F) to +45C (+113F)          |
| Replaceable Light Source : | No                                  |
| Number of LEDs :           | 36                                  |
| Connection:                | Direct Wired                        |
| Power Factor :             | >0.9                                |
| Voltage Type:              | Range Voltage                       |
| Warranty:                  | 5 Year Limited - Fixtures           |

## PACKAGING

|                  |                       |
|------------------|-----------------------|
| Each UPC:        | 045923112959          |
| Each Quantity:   | 1                     |
| Each Dimensions: | 8.19 x 3.94 x 8.27    |
| Case UPC:        | 10045923112956        |
| Case Quantity:   | 12                    |
| Case Dimensions: | 17.32 x 12.60 x 17.32 |

## INFO

Specification Note: \_\_\_\_\_ 360 degree rotation; 0 to 80 degree aiming angle

## PHYSICAL

|                |                   |
|----------------|-------------------|
| Finish:        | White             |
| Lens Finish:   | Frost             |
| Lens Material: | Plastic           |
| Finish Family: | White             |
| Dimensions:    | H:2.13" DIA:7.48" |
| Weight (Lbs.): | 1.22              |
| Material:      | Aluminum          |

## INSTALLATION

|                                |                |
|--------------------------------|----------------|
| Max Drywall Thickness:         | 1 in.          |
| Rec. Spacing Between Fixtures: | 3 ft. to 4 ft. |
| Clearance Height:              | 3              |

## IOT

|                   |                                    |
|-------------------|------------------------------------|
| IOT Enabled:      | Yes                                |
| What's Supported: | Google Home;Alexa;Siri;SmartThings |

## COMPLIANCE

|                            |                    |
|----------------------------|--------------------|
| Safety Listing:            | cETLus - Listed    |
| Location Rating:           | Damp               |
| Indoor/Outdoor:            | Indoor             |
| Energy Star Qualified:     | Yes                |
| Energy Star Unique ID:     | ESID-2470770       |
| Energy Star Lamp Category: | Downlight Recessed |
| CA Prop 65:                | Lead               |
| FCC Compliant:             | Yes                |
| IP Rating:                 | IP42               |
| RoHS Compliant:            | Yes                |
| SDS Class:                 | LED_Fixture        |
| Restrictions:              | No Restrictions    |

**ACCESSORIES**

---

**80-944**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 6-inch Recessed Downlights; Up to 6.25-inch hole diameter

---

**80-947**6" Goof Ring for Remote Driver Installation

---

**80-949**6 FOOT REMOTE DRIVER 1-PIN EXT

---

**80-951**New Construction Mounting Plate for Stud/Joist mounting of 6-inch Recessed Downlights; Up to 5.688-inch hole diameter

---

**86-216**Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts

---