

# WAC LIGHTING

## Downtown

### Round Outdoor Ceiling Mount

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W47204 3.5"	3500K 4000K	BK Black WT White	9.5W	863	333

Example: **FM-W47204-40-WT**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### FEATURES


- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- ADA compliant on 3inch version
- Conversion plate available to cover 4" junction box for the 3" size
- ACLED driverless technology
- 5 Year warranty

#### SPECIFICATIONS


<b>Color Temp:</b>	3000K,3500K,4000K
<b>Input:</b>	120 VAC,50/60Hz
<b>CRI</b>	90
<b>Dimming:</b>	ELV: 100-10% , TRIAC: 100-10%
<b>Rated Life:</b>	54,000 Hours
<b>Mounting:</b>	Can be mounted on ceiling or wall in all orientations
<b>Standards:</b>	ETL, cETL, Title 24 JA8 Compliant, Wet Location Listed
<b>Construction</b>	Aluminum body with acrylic diffuser



#### FINISHES:



#### LINE DRAWING



FM-W47204

# WAC LIGHTING

## Downtown

### Round Outdoor Ceiling Mount

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W47205 5"	3000K	BK Black WT White	11.9W	900	607
	3500K			925	647
	4000K			950	618

Example: **FM-W47205-40-WT**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### FEATURES


- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- ADA compliant on 3inch version
- Conversion plate available to cover 4" junction box for the 3" size
- ACLED driverless technology
- 5 Year warranty

#### SPECIFICATIONS


<b>Color Temp:</b>	3000K,3500K,4000K
<b>Input:</b>	120 VAC,50/60Hz
<b>CRI</b>	90
<b>Dimming:</b>	ELV: 100-10% , TRIAC: 100-10%
<b>Rated Life:</b>	54,000 Hours
<b>Mounting:</b>	Can be mounted on ceiling or wall in all orientations
<b>Standards:</b>	ETL, cETL, Title 24 JA8 Compliant, Wet Location Listed
<b>Construction</b>	Aluminum body, glass diffuser



#### FINISHES:



#### LINE DRAWING



FM-W47205