



## General Information

Type	spot
Product segment	Indoor
Theme	fabric-conzept
FSC®	FSC® Mix70% Hevea br FSC® C152762

## Dimensions

Article Height (in mm)	1100
Article Length (in mm)	335
Net Weight (in kg)	1.06 Kilogram
Article Overhang (in mm)	100
Article Width (in mm)	90
Article Diameter (in mm)	380
Canopy Length (in mm)	530
Canopy Width (in mm)	45
Canopy Height (in mm)	25
Base Diameter (in mm)	220
Base Length (in mm)	180
Base Width (in mm)	180
Installation Depth (in mm)	26
Cutout (in mm)	205
Canopy Diameter (in mm)	460

## Material & Colour

Enclosure Material	steel
Enclosure Colour	black
Glass/Shade Material	fabric
Glass/Shade Colour	black, gold
Cable Colour	black

## Functionality

Switch Type	without switch
Battery	No
Function	LED not replaceable
Battery Type	CR2032
Sensor Angle (in °)	120
Sensitivity min. (in lux)	30
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	15
Distance (in Meter)	6

## Technical Information

Protection Degree	IP20
Protection Class	1
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	2X28W
Dimmable	No
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz

## Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

## Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	3000K
Light colour Complete	WARM WHITE
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Energy efficiency class (EEI)	D
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Rated Lamp Power (0,1W precision)	36
Colour Tolerance (LED, SDCM)	<6
Lumen Complete	5100

## Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included



E27

2X28  
W