



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1415 - 20 Watt LED Dual Head Security Flood Light; 9.61 x 7.32 x 7.17; 80 CRI; 3000K/4000K/5000K CCT; Black Finish; Wet Location Rated

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	20W
Volts:	120V-277V
Lumens:	2600L/2700L/2900L
Lamp Base :	Integrated
Efficacy:	145.00 LPW
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Non-Dimmable
Incandescent Equivalent :	150W-200W
Operating Temperature :	-40F to +122F (-40C to +50C)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2KV
THD:	<20%
Power Factor :	>0.7
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923415623
Each Quantity:	1
Each Dimensions:	10.87 x 5.63 x 7.28
Inner UPC:	
Inner Quantity:	0
Inner Dimensions:	0.00 x 0.00 x 0.00
Case UPC:	10045923415620
Case Quantity:	5
Case Dimensions:	28.94 x 11.42 x 7.87

INFO

Integrated Features:	Integrated PIR Sensor
----------------------	-----------------------

PHYSICAL

Fixture Type:	Security Lighting
Finish:	Black
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Dimensions:	W:9.61" H:7.17" E:7.32"
Weight (Lbs.):	1.98
Material:	Die-Cast Aluminum
Sensor:	Built-in Photocell

INSTALLATION

Cord Length:	9 in.
--------------	-------

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions