



E26 Max 60W Not included

# Flush Mount Instruction

## Safety Warning

Turn OFF power at the breaker panel before starting. Use a non-contact voltage tester to confirm the wires are de-energized.

---

## Installation Steps

### • Step 1: Attach the Mounting Bracket

- Remove the cross-shaped mounting bracket from the fixture, if pre-attached.
- Hold the bracket against the ceiling junction box and fasten it with the two junction-box screws (provided). The two threaded posts on the bracket should point straight downward.

### • Step 2: Electrical Connections

1. Strip about ½ in. of insulation from fixture leads, if necessary.
2. Hot: Connect fixture black wire to house black (hot) wire.
3. Neutral: Connect fixture white wire to house white (neutral) wire.
4. Ground: Connect fixture green/bare wire to house ground/bare copper wire or the green ground screw on the bracket.
5. Tighten all wire-nuts clockwise and tuck the connections neatly into the junction box.
6. Twist each pair clockwise, cap with wire nuts, and gently push the wires up into the box.

### • Step 3: Secure the Socket Plate

Raise the rectangular socket plate up to the bracket. Align the slots over the two threaded posts and slide it into place. Thread the decorative nuts onto the posts and hand-tighten until snug.

### • Step 4: Install Light Bulb

Screw one E26 medium-base bulb (max 60 W, not included) clockwise into the socket until firmly seated.

### • Step 5: Position the Decorative Shade

Carefully lift the curved shade over the bulb. Align the side holes in the shade with the mounting holes on the socket plate.

### • Step 6: Lock the Shade in Place

Insert the two small side screws through the shade holes into the socket-plate holes and tighten just enough to secure the shade. Do not overtighten.

---

## Final Check

Restore power at the breaker panel and test the fixture. The shade should sit flush and level, and the bulb should illuminate without flicker.