



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-542 - LED Tempered Glass Flood Light with Bypassable Photocell; CCT Selectable 3K/4K/5K; Wattage Adjustable 45W/60W/80W; ColorQuick and PowerQuick Technology; Bronze Finish

- Wattage Selectable
- CCT Selectable
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	45W/60W/80W
Volts:	120V-347V
Lumens:	5400L-11200L
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	150x140
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
DimmableText:	0-10V Dimming Only
HID Equivalent :	150W-250W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 6KV
THD:	20%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923657979
Each Quantity:	1
Each Dimensions:	10.00 x 4.92 x 12.90
Case UPC:	10045923657976
Case Quantity:	4
Case Dimensions:	20.86 x 10.43 x 13.78

INFO

Specification Note:	NEMA Distribution: 7V x 7H
Installation Note:	Height will change with different mounting options.

PHYSICAL

Finish:	Bronze
Lens Material:	Tempered Glass
Finish Family:	Bronze
Dimensions:	L:9.65" W:3.07" H:9.65"
Weight (Lbs.):	2.44
Material:	Die Cast Aluminum
Sensor:	Has Photocell

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-HIQURN
DLC Primary Use:	Architectural Flood and Spot Luminaires
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP66
IK Rating:	IK08
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

65-542 - LED Tempered Glass Flood Light with Bypassable Photocell; CCT Selectable 3K/4K/5K; Wattage Adjustable 45W/60W/80W; ColorQuick and PowerQuick Technology; Bronze Finish

ACCESSORIES

**65-544**Trunnion Mount for Small/Medium Tempered Glass Flood Light ; Bronze Finish

**65-547**Yoke Mount for Medium Tempered Glass Flood Light; Bronze Finish

**65-549**Tempered Glass Flood Light Slipfitter Mount for Small and Medium Floods



65-542 - LED Tempered Glass Flood Light with Bypassable Photocell; CCT Selectable 3K/4K/5K; Wattage Adjustable 45W/60W/80W; ColorQuick and PowerQuick Technology; Bronze Finish

DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NTSTV-DV
Eaton	SF10P