

# PE2WL SERIES

## Wet Location LED Emergency Unit

### Specifications:

#### Description:

The PE2WL offers LED performance and value with a compact and attractive wet location LED based emergency light. The grey housing is made of corrosion resistant UV stabilized polycarbonate. Lamp-head consists of metalized high-performance reflector and 15 ultra-bright LED's with tempered glass lens. Includes external mounting brackets for ease of installation. The PE2WL has adequate capacity to run 1 each PEWLH double head or 2 PEWLH single-head remotes at 9.6 VDC for 90 minutes.

#### Features:

- LED life-cycle of more than 10 years
- Quick installation
- Dual-voltage 120/277V AC input
- Includes long-life 9.6 VDC Nickel Cadmium battery for UL recognized 90 minute operation
- Remote capacity for extended runtime
- Wet Location Listed (0°C to 50°C)
- Fully adjustable lamp-heads
- Provided with water-proof test switch and AC-on indicator

#### Application:

The PE2WL can be applied in areas that are susceptible to rain and severe moisture like pool areas, parking decks, and other commercial applications.

#### Energy Consumption:

Input	120 VAC	277 VAC
Watts	2.7W	2.7W
Amps	0.03A	0.013A

#### Accessories:

- PEWLH – SG – 82
- PEWLH – DB – 82




#### Catalog number:

Base	Material	Input	Finish
PE2WL	Thermoplastic	120/277	82 - Metallic Gray

#### Images:



#### Dimensions:



#### Warranty:

2 year full unit warranty

#### Compliances:

- UL924 Listed for Wet Location
- NFPA 101 and NFPA 70
- OSHA