

# RA Series / SE Series Latch Set





#### Material

Stainless Steel Levers and Escutcheons

#### Levers

All INOX Stainless Steel lever designs

# Finish

- · 630 Satin Stainless Steel (US32D)
- · 629 Bright Polished Stainless Steel (US32)
- · Two-tone Stainless Steel (SP)
- · 613 Oil Rubbed Bronze on Stainless Steel (10B) on selected lever designs
- \* See page 2.1 for finish availability.

#### Functions: Non-Keyed Lock



# Passage (L61/L71)

Both levers always unlocked.



#### Privacy (L62/L72)

Push privacy pin from inside to lock door.
Unlock latch by turning inside lever or by emergency release from hole in outside rose cover.



# Half Dummy Left (DL) or Half Dummy Right (DR)

Left or Right levers always inactive. Optional working dummies available by specifying "WORKING".



# **Communicating (CM)**

Inside lever always unlocked, outside dummy plate escutcheon. Usually used on connecting room doors.

#### **Application**

For residential interior doors with passage, privacy, or dummy application.


#### **Features**

- · Standard door preparation
- · Strong spring chassis
- · Concealed bolt-thru or screws fixing

### Specification


- · Door Thickness:
- 1-3/8" (35mm) to 1-3/4" (44mm) Thick Door Kits Available
- · Backset: 2-3/8"(60mm) standard 2-3/4" (70mm) optional.
- · Handing: Field reversible latch for passage and privacy function.
- Specify handing for single dummy and exit/communicating function.
- · Spindle: 5/16" (8mm) square
- · Tubular Latch with 8x8mm hub
- · Faceplate and strike plate with square corners. Radius corners available on
- · UL fire rated latch available.

# **Door Preparation**




# Rose

#### **RA Rose**



#### SE Rose



<sup>\*</sup> Note: Communicating function handing specified from outside where this is no lever. i.e. For a Left Handed (LH) communicating set, the inside lever will be a Right Hand lever.