SHORT INSTRUCTION FOR DARSTORY PRODUCTS

EN SCAN THE OR CODE TO ACCESS THE DETAILED INSTALLATION AND USAGE INSTRUCTIONS FOR THE PRODUCT



SHORT INSTRUCTION FOR DARSTORY PRODUCTS

SAFETY DURING INSTALLATION AND USAGE
DABSTORY s.c. maintains that the products it sells, when properly installed and used in accordance with their intended purpose and the user manual, can be used safely.

Installation should be carried out by adults only. Products may contain small parts that pose a risk of choking or swallowing. These products are not certified as items intended for children. Warning! Do not install the product if you notice any missing parts, defects, or damage to the purchased product or its components. During use, parts, cerects, or damage to the purchased product or its components. During use, regularly inspect the product's overall condition and ensure that fastening components have not become loose. Overloading the product may pose safety risks and lead to permanent damage. Exercise caution, especially in humid environments, which can increase the risk of slipping and falling.

GENERAL INSTALLATION GUIDELINES

Before starting the installation, carefully review the detailed instructions and maintenance guidelines for the product (available via the QR code at the top of the page – if you encounter any issues accessing it, please contact us). It is crucial to follow the installation steps in the correct order (see the last page for installation methods according to the numbering helow)

1. <u>Products Mounted with Screws and Wall Pluss:</u>
Minimum wall thickness: 10 mm. Maximum product load: 1 kg for every 10 cm of product width. The set includes mounting components designed for materials such as standard concrete, ceramic brick, silicate brick. hollow silicate brick, ceramic blocks, autoclaved aerated concrete, and drywall (G-K)*. **Note:** If the wall material in your home differs from the ones listed, consult a local hardware store to select appropriate screws. When drilling holes, follow health and safety regulations by wearing protective goggles and gloves. *Exception: Drywall (G-K) is not suitable for mounting the Ricobi double towel rack

2. Products Mounted with Adhesive Tages Maximum shelf lead: 1 kg for every 13 cm of shelf width. Maximum hook load: 3 kg. The product can be mounted on the following materials: ceramic, PVC, aluminum, and Iscupered wood. Noted Mounting surface surface. Surface with the companies of the compa installation, ensure that the surface (wall) is suitable for adhesive tape mounting.

Hanging Products

nickness of the shower nanel or the width of the hathtub is suitable for the installation method suggested by the manufacturer.

Do not use abrasive sponges or cleaning agents containing abrasive materials, as they may dull or scratch the surface. Avoid using cleaners that contain solvents, acids, or vinegar. Always test any cleaning agent on an inconspicuous area before use. Clean the product surface with a soft cloth or paper towel.

WARRANTY

DABSTORY s.c. provides a warranty to consumers for DABSTORY brand products. The warranty covers only defects arising from issues inherent to the sold product. The warranty period is a minimum of 2 years* from the date of purchase and is valid worldwide. The warranty does not exclude. suspend, or limit the consumer's rights under statutory warranty provisions for defects in sold goods. If a defect is found in the product, consumers may file a complaint via email at bok@dabstory.com, through the complaint form available on the store's website, or by contacting the seller on the sales platform. DABSTORY s.c. is not responsible for damages or defects beyond the scope of the provided warranty.

*Scan the QR code at the top of the page to check the warranty period for your product in the detailed user manual.

