



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-634 - Square LED; Wide Beam Angle Canopy Light; 3K/4K/5K CCT Selectable; 20W/30W/45W Wattage Selectable; White Finish

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	20W/30W/45W
Volts:	120V-277V
Lumens:	2663L-6288L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Color Description:	Warm White to Natural Light
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming
Operating Temperature :	-40C (-40F) to +50C (+122F)
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2.5KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923654176
Each Quantity:	1
Each Dimensions:	11.02 x 5.12 x 11.02
Inner UPC:	20045923654170
Inner Quantity:	0
Inner Dimensions:	0.00 x 0.00 x 0.00
Case UPC:	10045923654173
Case Quantity:	4
Case Dimensions:	21.18 x 11.61 x 11.81

INFO

Additional Info:	Recommended Mounting Height: 9 to 15 Feet
Specification Note:	Multiple half-inch knockouts; Three quarter inch back knockout for pendant applications
Installation Note:	Hinged door for ease of installation
Integrated Features:	Integrated DC Sensor Port

PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	L:9.57" W:9.57" H:3.62"
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-32C65E
DLC Primary Use:	Parking Garage Luminaires
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK10
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

ACCESSORIES

**65-633**Add on Emergency Backup Battery for LED Wide Beam Angle Canopy Light Fixtures; 8 Watt; Black Finish

**86-217**Add-On PIR Sensor; 6 Meter

**86-218**Add-On Microwave Sensor; 12 Meter

**86-219**Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors

**86-220**Add-On PIR Sensor; 12 Meter
