

CLOCK HANGING INSTRUCTIONS

You
will
need:



Screw Driver



Measuring Tape



5 Screws
(included in your order)

Thank you for your order! Each sale of Designart artwork helps an artist live through their passion.

Step 1:

Determine where you would like to hang your new clock.

Your clock has the wall hanging bracket built directly into the actual wood frames.

The top part of each frame is designed with a lip, which you will hang over the included screws.

We recommend using 2-4 screws, depending on the size of your clock.

Step 2:

Set the time by manually moving the clock hands. Once you have set the correct time, insert the included battery in the back of the clock.

The clock should start ticking as soon as the battery is installed.

Step 3:

Once the clock is ticking, turn your first screw in the wall in the desired place.

Use a measuring tape and mark the placement of your second screw, turn the second screw into the wall. Repeat until desired number of screws has been installed. Finally, hang your new clock over the installed screws.


Trouble Shooting: All of our clocks have been tested prior to shipping.

If you install the battery and the clock is not working, please take the following steps.

1. Verify the battery is installed in the correct direction

2. Try another battery (we include brand new batteries but a defective battery is always possible)

3. Make sure the clock hands are securely fitted on the corresponding rings of the clock face. If they have moved during transit and are no longer in the correct place, the clock will not work. Adjust them until they click into place.



Lip for hanging over screws

