

R4RD1L, R4SD1L

4.5" Volta

Shallow Regressed Downlight Invisible Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- Increased field angle for reduced scalloping
- Low ceiling and close-to-wall applications
- Field selectable light engine height for cut-off angle adjustment (32° - 40°) and accessory use
- Integral patterned tempered trim lens included standard
- Compatible with wide range of accessories
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input: Universal 120 - 277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-5% (120V only)
0-10V: 100%-0% (120 - 277V)

Light Source: High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly. Safety cabling standard.
Ceiling cut out (Round): Ø 5 1/8"
Ceiling cut out (Square): 5 1/8" x 5 1/8"
Accommodates 1/2" - 1 1/2" ceiling thickness

Finish: Electrostatically powder coated White, Black. Enamel coated Haze.

Standards: ETL & cETL Wet location Listed

TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*			Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	CBCP	Lumens/Watt				
 R4RD1L <i>Round</i>	S 15°	1390	12200	60	827 2700K 85 927 2700K 90 830 3000K 85 930 3000K 90 835 3500K 85 840 4000K 85	BK HZ WT	<i>Black</i> <i>Haze</i> <i>White</i>	
	N 25°	2678	8866	74				
	F 45°	2422	4261	67				
	W 60°	2321	2505	64				
 R4SD1L <i>Square</i>	S 15°	1436	12664	62				
	N 25°	2797	8556	78				
	F 45°	2762	4779	77				
	W 60°	2563	2445	71				

*Reference output shows **830**(85CRI 3000K) trim with **36** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
HOUSING 36	0.937	0.764	1.000	0.815	1.045	1.054
25	0.685	0.558	0.731	0.596	0.764	0.770
15	0.456	0.371	0.486	0.396	0.508	0.512

R4_D1L-_____ - _____

Example: **R4RD1L-S827-WT**

Please see next page for housing units(required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R4RD1L, R4SD1L

4.5" Volta

Shallow Regressed Downlight Invisible Trim

WAC LIGHTING

Responsible Lighting®

HOUSINGS (REQUIRED)

		Model	Power*	S	N, F, W	Rating	Emergency Backup								
<p>Round New Construction</p>	R4RNL <i>Airtight</i> R4RCL <i>Airtight, Chicago Plenum</i>	15 25 36	10W 15W 23W	15W 25W 36W	<i>IC rated</i> <i>IC rated</i> Non-IC	EM	<i>Emergency backup battery (OPTIONAL)</i>								
								<p>Square New Construction</p>	R4SNL <i>Airtight</i> R4SCL <i>Airtight, Chicago Plenum</i>	15 25 36	10W 15W 23W	15W 25W 36W	<i>IC rated</i> <i>IC rated</i> Non-IC	EM	<i>Emergency backup battery (OPTIONAL)</i>

*Power consumption depends on beam angle of the trim.

Field Replaceable Driver

D-R4N-15	Driver for 15W New Construction Hsg
D-R4N-25	Driver for 25W New Construction Hsg
D-R4N-36	Driver for 36W New Construction Hsg

R4 _____ - _____
 Example: **R4RNL-15** or **R4RNL-15EM** (with Emergency backup battery)

Invisible Trim housings come included with die-cast spackle frame.

FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM

Accessory holder
 Holds up to two lenses or
 One lens and one glare control

Optical cartridge
 Allows tool-less exchange of reflectors



Reflector
 For narrow flood, flood, and wide flood.
 Spot distribution features dedicated module.

Accessory holder

LENS-73-HLD Required to hold lens and glare control accessories

Glare control accessories
LENS-73-HCL Honeycomb Louver
LENS-73-CRL Cross Louver

Lens

LENS-73-AMB Amber lens
LENS-73-RED Red lens
LENS-73-FR Frosted lens
LENS-73-SPR Spread lens
LENS-73-BEL Beam Elongating

Interchangeable Reflector

REF-R4-N Narrow beam reflector
REF-R4-F Flood beam reflector
REF-R4-W Wide beam reflector

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760