outline drawing:



model:

Technical data: Power supply voltage 110-120V, bulb type E26Max40Wx4PCS (not included)

CAUTION

- Before installing the lighting fixtures, please check the insulation of the wires for any cuts, wear, or possible damage during transportation。If the wires are defective, do not attempt installation 。
- In some countries, electrical installation work can only be carried out by authorized electrical contractors。Please contact the local power department for advice。



IMPORTANT Before starting the installation work, please make sure to cut off the power supply to the circuit。

IMPORTANT Keep children away from the installation process 。

Required tools (not included):



Ladder



Phillips screwdriver

pincers

Required tools (including):

Hex Wrench

glove

The hardware kit provides:



sling chain

Hanging plate screws

mounting screw

carabiner

ring

CONNECTORS

tray

Installation board



Welding frame

Welding decorative tubes -4pcs



Lamp rack

Welding U-shaped frame

Welding main body frame

cable tie



Gecko rubber stopper



Self tapping screws

• The components displayed on each lamp may vary slightly

step 1



① Thread the screw through the hole on the welding frame and connect it to the tooth hole on the welding decorative tube, and tighten it. Install the remaining part according to this step。

step 2



① Thread the screw through the hole on the welding body frame and tighten it to connect it to the lamp frame。

step 3



① Connect the screw through the hole on the welding body frame and the tooth hole on the welding frame, and tighten it。

② Connect the screw through the hole on the U-shaped welding frame and the tooth hole on the welding frame, and tighten it。

③ Tighten the hanging ring and the tooth rod on the welding body frame。

Step 4



① Thread all the wires through the canopy and installation kit。

② Connect the power cable with two cable connectors。

③ Connect the grounding wire and tighten it with the grounding screw。

④ Install the fixing screws into the mounting plate, install the installation unit under the junction box, and tighten with two mounting screws。

⑤ Fix the canopy in place using a suspension ring. Tighten the screw ring and hex nut with a wrench to tighten the hex nut。

⑥ Tighten the fixing screws on the rain shelter holes。

⑦ Tighten the cap tightly。



Connect the black or red wire (with an L sticker on the wire) to:	Connect the white wire (with N stickers on the wire) to:
black	white
Parallel lines - pti&l (circular and smooth)	Parallel lines - spri&l (square and ridge shaped)
Transparent, brown, gold or black (without tracer)	Transparent, brown, gold or black (with tracer)
Copper core insulated wire (excluding GREEN)	Silver conductor insulated wire (excluding GREEN)



Step 5



①② This depends on the height of your ceiling and the desired suspension length. You can measure the chain and adjust the locking buckle to achieve the desired chain length。

③ Tighten the light bulb (E26 maximum 40W, not included)。