



# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING: Turn off the main power at circuit breaker before installing fixture.**  
**AVERTISSEMENT: Coupez la source d'alimentation principale au panneau central de disjoncteurs avant d'installer le luminaire.**

**NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.**  
**2. Read and save these instructions.**

## Hardware Package (included):



## Installation Steps

**Turn off the power at fuse or circuit box.**

1. Unscrew the four set screws (D), remove the four rubber pads (E) and the mounting plate unit (A) from the backplate.
2. Attach the mounting plate unit (A) to the outlet box by using two mounting screws (B).  
**Note: Make sure that top two set holes are lined up horizontally to make the fixture level.**
3. Pull out the source wires from the outlet box. Make wire connections using wire connectors (C) as follows:
  - Connect the hot wire (black insulation) from the fixture to the black wire from the power source.
  - Connect the neutral wire (white insulation) from the fixture to the white wire from the power source.
  - Attach the fixture ground wire (bare wire) to the mounting plate (A) with green ground screw, then depending on local code, connect it to the house ground wire with the wire connector (C).Carefully put all of the wires back into the outlet box.

4. Attach the backplate of the fixture to the mounting plate unit (A) by aligning into set holes on backplate, then secure it with four rubber pads (E) and four set screws (D).

**Note: With silicone caulk compound, caulk completely around where the backplate meets with the wall surface to prevent water from seeping into the outlet box.**

5. Install the bulb (not included). See relamping label at socket area or packaging for maximum wattage allowed.


6. Rotate the glass shade onto the glass holder to the fixture.

**Turn on the power at fuse or circuit box.**

**The following parts are available for reorder if damaged or missing.**

**Spare Parts List:**

The diagram shows a collection of spare parts for the fixture. On the left is the Mounting Plate Unit (A). Next to it are two Mounting Screws (B). Then there are three Wire Connectors (C). Following are four Set Screws (D). Then there are four Rubber Pads (E). An arrow points from these parts to an Assembly Kit 6722MM (1 SET). To the right of the assembly kit is a Glass Shade 10380CG.



### 1 Year Warranty

We warrant all of our products against defects in workmanship and finishes for one year following the date of shipment.

*Exclusions: This warranty does not include the failure of products from extreme acts of nature; environmental conditions not suited for the products intended use; operation in temperatures outside of the range specified in the instruction manual; usage with improper power supply, power surges or dips. For coastal locations, some corrosion is considered normal for the environment.*

*We reserve the right to repair, replace or issue a credit for any properly installed product, provided it is returned per RMA instruction. This warranty is limited to the cost of the product only and does not extend to transportation, installation or replacement costs.*