

**F24815**

**F24784**

**F24785**


## Grey rubber industrial caster

Grey rubber caster, rigid or swiveling, available with or without break.



### Advantages and benefits

- Non-marking rubber tread.
- Corrosion-resistant zinc finish
- Protective metal thread guards.
- Two independent rows of hardened, polished precision ball bearings roll freely and silently in large-diameter lubricated raceways.

### Non-marking tread:



Carpet



Tile / Linoleum / Ceramic

### Conditions :

- *Water: Optimal*
- *Solvents: Efficient*
- *Detergents: Efficient*
- *Acids: Not recommended*
- *Extreme cold: Not recommended*
- *Extreme heat: Efficient*
- *Petroleum products: Efficient*

### Recommended surfaces:



Product number	Description	Wheel Diameter	Load Capacity	Tread Width	Overall Height
<b>F24784</b>	Swiveling caster, without break	50mm (2")	40 kg (88 lbs)	18 mm (11/16")	73 mm (2-7/8")
<b>F24785</b>	Swiveling caster, with break	50mm (2")	40 kg (88 lbs)	18 mm (11/16")	73 mm (2-7/8")
<b>F24814</b>	Rigid caster, without break	50mm (2")	40 kg (88 lbs)	18 mm (11/16")	73 mm (2-7/8")
<b>F24786</b>	Swiveling caster, without break	75mm (3")	60 kg (132 lbs)	21 mm (13/16")	103 mm (4-1/16")
<b>F24787</b>	Swiveling caster, with break	75mm (3")	60 kg (132 lbs)	21 mm (13/16")	103 mm (4-1/16")
<b>F24815</b>	Rigid caster, without break	75mm (3")	60 kg (132 lbs)	21 mm (13/16")	103 mm (4-1/16")