# DIONE

design atelier oï 2025

## Model SP 1 G_UL

Collection composed of two satin white glass discs of different diameters, which can be combined together or used individually with a third element at the base that houses the two integrated LED sources designed for dual switching. These elements, which can be arranged in various configurations, are connected by electrical cables along which the glass diffusers used in pairs or individually can be positioned at the desired height, creating ever-changing compositions and visual balance.



DIONE SP 1G BCST NNS L22 UL

**GLASS FINISH**



**BCST**
**white matt**

**FRAME FINISH**



AVS
matt steel



**NNS**
**matt black nickel**




**LIGHT SOURCES**

**1x12+14W 120V/60Hz LED 2700K 12W+14W 3500 DIM2 Phase Cut**
1x12+14W 120V/60Hz LED 2700K 12W+14W 3500 DIM3 0-10V Push
1x12+14W 120V/60Hz LED 3000K 12W+14W 3500 DIM2 Phase Cut
1x12+14W 120V/60Hz LED 3000K 12W+14W 3500 DIM3 0-10V Push

**TECH DATA**

IP20

VOLUME: Mc 0,10
PACKAGE: N.1
NET WEIGHT: Kg 4,80
GROSS WEIGHT: Kg 8,00

**CERTIFICATIONS**

International Cert