

## **PENDANT FIXTURE** **INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them a later date.

### **CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### **GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### **ASSEMBLY AND INSTALLATION**

- Connect the Pipe (1),(2),(3),(4) (5) together with the fixture. Then screw with the Swivel.
- Attach two Screws-1 outward through the CROSS BAR, spin the Hex nut to the Screw-1, then attach the CROSS BAR(6) to the OUTLET BOX by the two MOUNTING SCREWS.
- Make wire connections:
  - Twist together the white wire from the fixture with the white wire from outlet box. Cover with wire connector
  - Twist together the black wire from the fixture with the black wire from outlet box. Cover with wire connector
  - Loop the GROUND WIRE to CROSS BAR with a GREEN SCREW
- Place the CANOPY against the OUTLET BOX by screwing the Hex nut and Ball Nut
- Put the shade ( Not included) onto the socket, then use socket ring screw tightly.
- Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).

INSTALLATION IS NOW COMPLETED.

