

Installation Guide

Please follow the steps below to safely assemble and install your fixture.

Easy Installation Steps

How to assemble the adjustable swivel joint



Step 1: Loosen the side knob and open the swivel joint.



Step 2: Insert the rod end into the swivel joint opening.



Step 3: Tighten the knob to secure the rod.



Step 4: Remove the top cap from the canopy joint.



Step 5: Insert the upper rod into the canopy connector.



Step 6: Tighten the knob and adjust to the desired angle.

Important Safety Notes

- Turn off power at the circuit breaker before installation.
- We recommend installation by a licensed electrician.
- Use Type A / E26 bulbs, maximum 60W (bulb not included).

Step 1: Prepare the Fixture

Remove all components from the package and confirm all parts are included before installation.

Step 2: Assemble the Adjustable Swivel Joint

1. Loosen the side knob and open the swivel joint.
2. Insert the rod end into the joint opening.
3. Carefully guide the wires through the joint.
4. Make sure wires are placed inside the groove to prevent damage.
5. Tighten the knob to secure the connection.

Step 3: Install the Mounting Plate

Secure the mounting plate to the outlet box using the provided screws. Make sure it is firmly attached.

Step 4: Connect the Wires

Connect wires according to color:

- Black wire to black supply wire.
- White wire to white supply wire.
- Ground wire to ground wire.

Secure all connections with wire connectors.

Step 5: Secure the Fixture

Attach the fixture body to the mounting plate and tighten the nuts to secure it in place.

Step 6: Install Shade and Bulb

Install the shade onto the socket, tighten the retaining screws, then install the bulb.

Step 7: Adjust Fixture Direction

Loosen the swivel joint knob, adjust to the desired angle, then tighten the knob to lock the position.

Cleaning & Care

Clean with a soft dry cloth. Do not use abrasive cleaners or harsh chemicals.