



Cimarron® | K-31614-DRY

Toilet tank, 1.6 gpf

Features

- 1.6 gpf (6.0 lpf)
- Left-hand Polished Chrome trip lever
- Combines with the K-31588 or K-31589 bowl to create a complete K-31620-DRY or K-31640-DRY Cimarron® toilet
- AquaPiston® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling



Available Colors/Finishes

Color tiles intended for reference only.

- | | | |
|---|----|---------|
|  | 0 | White |
|  | 96 | Biscuit |



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-30-2026 05:20 - US-CA

THE BOLD LOOK
OF **KOHLER**®

Codes/Standards

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

ASME A112.19.2/CSA B45.1

Technical Information

Flush Type: AquaPiston, Revolution 360

Flush Rate: 1.6 gpf (6.0 lpf)

Recommended Products/Accessories

K-31588 Elongated toilet bowl

K-31589 Round-front toilet bowl

K-25986-L Left-hand trip lever

Warranty

See website for detailed warranty information.

KOHLER® One-Year Limited Warranty



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-30-2026 05:20 - US-CA

No image available.

This product is a component and not intended to be a standalone installation.

Installation

- DryLock™ system saves installation time and helps prevent water leakage
-

Installation Notes

Install this product according to the installation instructions.

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

