Step-by-Step Slipcover Installation

1. Prepare the Fabric: Place the slipcover in the dryer on a low-heat or short cycle with a damp hand towel for a few minutes to help release any wrinkles from packaging. Remove any throw pillows and separate the seat cushions, if applicable.

2. Drape and Align: Position the slipcover over the top of the sofa. Align the upper back corners of the slipcover with the corresponding corners of the sofa.

3. Fit the Arms: Pull the fabric down over both armrests, making sure any contoured seams or rounded edges align properly with the shape of the sofa.

4. Secure the Bottom: Pull the bottom edge around the base of the sofa. Adjust the fabric so the front skirt or bottom band hangs evenly above the floor.

5. Tuck and Smooth: Work any excess fabric into the crevices between the backrest, arms, and seat cushions. Use your hands or a suitable tucking tool to smooth the fabric and achieve a neat, secure fit.

Triangle Leg Installation Instructions

If the predrilled holes cannot be located, please follow these steps:

1. Position the Furniture: Carefully turn the furniture onto its back or side to access the underside of the frame.

2. Locate the Mounting Area: Identify the designated mounting location for the triangle leg.

3. Position the Leg: Place the triangle leg against the furniture frame, ensuring it is properly aligned and sits flush against the frame.

4. Attach the Leg: If the predrilled holes are not visible, position the leg in the designated mounting area and use the provided screws to secure it directly to the furniture frame.

5. Tighten Securely: Carefully tighten each screw until the leg is firmly attached. Avoid overtightening.

6. Repeat: Repeat these steps for the remaining legs. Once all legs are securely installed, carefully return the furniture to its upright position.

Important: Ensure all legs are securely attached before using the furniture.