



SANIFLUSH ROUND TOILET BOWL

Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

SANIFLUSH 003 & 005

◆ 003 Round Bowl

- Vitreous China
- Integral P-trap and a spigot rear outlet
- Seating Height: 16-3/4"
- Large 3" trapway
- Wash down style toilet
- Low flush toilet; it uses 1.28 gallons (4.8L) per flush
- Toilet supplied with a set of lag screws, plastic anchors and china protectors
- Water spot measures 6 x 5 inches
- 1 Year Warranty

◆ 005 Tank

- Vitreous China
- Insulated tank to prevent condensation
- The zero re-fill fill valve is easily adjustable
- The flush valve has a silicone flapper seal
- Water level mark applied to the overflow tube
- Toilet tank supplied with bowl screws, washers and wing nuts.
- 1 Year Warranty
- Warranty for fill and flush valve as per manufacturer.

Nominal Dimensions:

32" x 17-3/4" x 26-1/2"
(813mm x 451mm x 673mm)

Fixture Dimensions and Hydraulic Performance – Meets or Exceeds the Following Specifications

- ANSI/ASME A112.19.2M and CAN/CSA B45 Requirements
- IAPMO/UPC Certificate of Listing

Notes

- Available in white only
- Toilet Seat Recommended – Church model 300SLOW or equal. (not supplied)
- Replacement Fill Valve Recommended – Fluidmaster 400A or equal. (not supplied)



Round Bowl with Tank (003 & 005)

Care & Cleaning

- When cleaning toilet, wash it with mild soapy water or liquid cleaners that are not chlorine or bleach based. Avoid using detergents.
- We do not recommend the use of in-tank cleansers. Products containing chlorine can cause damage to the fittings inside the tank and cause them to fail prematurely.





SANIFLUSH ROUND TOILET BOWL

Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

SANIFLUSH 003 & 005

Drawings and Dimensions

