
Project:

Spec Sheet

Description: Compact luminaires direct light down from the pure geometry of a rectangular prism. Also available as a $\frac{\text{Bollard}}{\text{Bollard}}$ and $\frac{\text{Double Bollard}}{\text{Double Bollard}}$.

Type #:





Dimensions

Height:	4.5"
Width:	3.5"
Extends:	2.5"
Minimum Extension:	2.5"
Maximum Extension:	2.5"
Canopy/Backplate/Base Width:	3
Canopy/Backplate/Base Depth:	0.5
Canopy/Backplate/Base Height:	4.25

Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	1
Input Voltage:	120VAC
Wattage:	10
Initial Lumens:	1020
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Outlet Box
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	10

Installation

Installation:	Licensed electrician
	required
Installation Orientation:	Vertical

Shipping

Carton 1 L x W x H:	6" X 7" X 6'
Carton 1 Gross Weight:	2 LBS
Fixture Weight:	1.5

Shade

Shade 1 Material:	Diecast
	Aluminum

Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

General Listings

Features:	Wet Rated
Certification: Color/Finish:	C-ETL-US Textured
Dark Sky Friendly:	White (.98) Y