



Tea-for-Two® | K-856-JHN

66" x 36" drop-in/undermount whirlpool bath

Features

- Six Proflex® hydromassage jets can be individually adjusted for water flow and direction
- Built-in heater
- Spacious design accommodates up to two bathers
- Integral lumbar support
- Multiple pump location options give you more choices for installation and access
- Textured bottom surface
- Single-speed whirlpool offers performance and value, with six fully adjustable jets
- Safeguard® slip-resistant surface provides excellent traction underfoot



Sustainability



Available Colors/Finishes

Color tiles intended for reference only.

0	White
96	Biscuit
NY	Dune
7	Black Black



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-30-2026 01:54 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

ASME A112.19.1/CSA B45.2
ASME A112.19.7/CSA B45.10
ASTM F462
UL 1795
CSA C22.2 No. 218.2
cUL Listed
UL Listed

Technical Information

All product dimensions are nominal.

Drain Location:	Reversible
Drain Hole Diameter:	2-1/4" (56 mm)
Minimum Flat for Door:	1-15/16" (50 mm)
Basin Area, Bottom:	44-5/8" x 25-3/8" (1133 mm x 645 mm)
Basin Area, Top:	58-9/16" x 28-7/8" (1488 mm x 733 mm)
Water Depth:	18-15/16" (481 mm)
Water Capacity:	108 gal (408.8 L)
Minimum Floor Load:	60 lbs/ft²
Weight:	485 lbs (220 kg)
Cutout:	Drop-in, 64-1/2" x 34-1/2" (1638 mm x 876 mm)

Material

- KOHLER® enameled cast iron

Required Products/Accessories

- K-23857 Bath drain trim
- or
- K-78440 33" cable pop-up bath drain

Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump:	120 V, 15 A, 60 Hz
Heater:	120 V, 15 A, 60 Hz

Electrical Component Ratings

Pump:	120 V, 7 A, 60 Hz
Number of Speeds:	Single
Heater:	120 V, 12 A, 60 Hz

Warranty

See website for detailed warranty information.


KOHLER® Hydrotherapy Components Five-Year Limited Warranty|KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty

Recommended Products/Accessories

K-1179 Tiling-in bead, 180" length
K-587 Undermount kit for select 66" Tea-for-Two bath models
K-23726 Drain treatment
K-23725 Cast iron cleaner
1015255 Jet Trim Kit



No change in measurements if connected with drain illustrated. (K-23856-NA)



Installation

- Drop-in or undermount
- Reversible drain

Installation Notes

Install this product according to the installation instructions.

Measure your actual product for rough-in details.
The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

